Form 9-331 a (Feb. 1951)

I

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office State Ie
Lease No. SF 04.7039 (b)
Unit Day Gas Unit

SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOTTING ALTERING CASING. OTICE OF INTENTION TO CHANGE PLANS. SUBSEQUENT REPORT OF SHOTTING ALTERING CASING. OTICE OF INTENTION TO REDEILL OR REPAR WELL SUBSEQUENT REPORT OF ALTERING CASING. OTICE OF INTENTION TO SHOOT OR ACIDIZE SUBSEQUENT REPORT OF ALTERING CASING. OTICE OF INTENTION TO SHOOT OR ACIDIZE SUBSEQUENT REPORT OF ALTERING CASING. OTICE OF INTENTION TO SHOOT OR ACIDIZE SUBSEQUENT REPORT OF ALTERING CASING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) AY GAS Unit FARKINGTON, New Maxico (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) AY GAS Unit FARKINGTON, New Maxico (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) AY GAS Unit FARKINGTON, New Maxico (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) AY GAS Unit FARKINGTON, New Maxico (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, N		AND REPORTS ON WELLS
SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING. STREED OF INTENTION TO TEST WATER SHUT-OFF. SUBSEQUENT REPORT OF ALTERING CASING. OTICE OF INTENTION TO TEST WATER SHUT-OFF. SUBSEQUENT REPORT OF ALTERING CASING. OTICE OF INTENTION TO SHOOT OR ACIDIZE. SUBSEQUENT REPORT OF ALTERING CASING. OTICE OF INTENTION TO PULL OR ALTER CASING. OTICE OF INTENTION TO DEAD ALTER CASING. OTICE OF INTENTION TO DEAD ALTER CASING. OTICE OF INTENTION TO ABANDON WELL. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) AND I IS located PROPERTY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) AND I IS located PROPERTY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT. (INDICAT	OTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHIFT-OFF
Subsequent report of Altering Casing. OTICE OF INTENTION TO RE-DRILLING OR REPAIR WELL SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR. OTICE OF INTENTION TO RE-DRILLING OR REPAIR. OTICE OF INTENTION TO PULL OR ALTER CASING. OTICE OF INTENTION TO PULL OR ALTER CASING. OTICE OF INTENTION TO PULL OR ALTER CASING. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) IN GRAPH OF Section 7 1-26-N Repair (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) IN O. 1 is located 990 ft. from S line and 1190 ft. from E line of sec. 7. (Indicate Above By Check Mark Nature of Report, Notice, OR Other 31 19 IN O. 1 is located 990 ft. from Repair (In Office of Intention of October 31 19 IN O. 2 Section 7 1-26-N Repair (In Office of Intention of October 31 19 In O. 3 Section 7 1-26-N Repair (In Office of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Note of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Note of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Note of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Note of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Note of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of Note of Intention of October 31 19 In O. 4 Section 7 1-26-N Repair (In Office of Intention of October 31 19 In Office of Intention of October 31 19 In Office of Intention of October 31 19 In Office of Intention	OTICE OF INTENTION TO CHANGE PLANS	
Subsequent report of re-Drilling or Repair. Subsequent report of re-Drilling or Repair. Subsequent report of Repair. Subsequent report of Repair. Subsequent report of Repair. Subsequent report of Asanconnent. Supplementary well history. (Indicate above by check mark nature of Report, Notice, or other data) Farmington, New Mexico October 31. 19 Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Subsequent report of Repair. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Subsequent report of Repair. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Subsequent report of Repair. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of sec. 7. Supplementary well history. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of State of Territory. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of State of Territory. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline and 1190. ft. from Eline of State of Territory. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of State of Territory. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eline of State of Territory. Il No. 1. is located 930. ft. from Eline and 1190. ft. from Eli	OTICE OF INTENTION TO TEST WATER SHUT-OFF	
Subsequent report of Abandonment. Supplementary Well History. (Indicate Above by Check Mark Nature of Report, Notice, or other Data) (Indicate Above by Check Mark Nature of Report, Notice, or other Data) Ly Gase Unit Farmington, New Market October 31 19 Ill No. 1 is located 990 ft. from Siline and 1190 ft. from Elline of sec. 7. (Indicate Above by Check Mark Nature of Report, Notice, or other Data) Ill No. 1 is located 990 ft. from Siline and 1190 ft. from Elline of sec. 7. (Indicate Above by Check Mark Nature of Report, Notice, or other Data) Ill No. 1 is located 990 ft. from Siline and 1190 ft. from Elline of sec. 7. (Indicate Above by Check Mark Nature of Report, Notice, or other Data) (Indicate Market Nature) (Indicate Data) (Indicate Data	OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	II
Supplementary well history (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) BY Gas Unit Farmington, New Maxico Cetober 31, 19 II No. 1 is located 990 ft. from Siline and 1190 ft. from Maxico Cetober 31, 19 II No. 2 section 7 7-26-N (Rango) (County or Subdivision) Read Peak Dakota Sam Juan Rew Maxico (Field) (County or Subdivision) (County or Subdivision) (State or Territory) et elevation of the derrick floor above sea level is 1844 ft. DETAILS OF WORK to names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centred and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centred that the stage with 275 sacks 65 gel mixed with 1-1/2 pounds Taf Plug per sack followed by 100 sacks next sement. Tested water shut off with 30% of for 15 minutes with no pressure drop. With stage tool set at 21621, mental second stage with 150 sacks 45 gel. Tested water shut off with 30% of for 15 minutes and no indication of pressure drop. Resumed completion herations. Box 460 Farmington, Max Maxico	OTICE OF INTENTION TO SHOOT OR ACIDIZE	
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) If INO. 1 is located 990 ft. from Siline and 1190 ft. from Mexico Ostober 31 190 line of sec. 7. If INO. 2 Section 7 1-22-N	OTICE OF INTENTION TO PULL OR ALTER CASING	1 11
Farmington, New Mexico Cetaber 31, 19 Il No. 1 is located 990 ft. from Siline and 1190 ft. from Eline of sec. 7. (Control of Sec. 100.7 (100.0) (Range) (Meridian) (Range) (Range) (Meridian) (Meridian) (Meridian) (Range)	OTICE OF INTENTION TO ABANDON WELL	
Il No. 1 is located 999 ft. from S line and 1190 ft. from S line of sec. 7. (K Sec. and Sec. No.) (Range) (Range) (Range) (Range) (Range) (Meridian) (Range) (Range) (Range) (Meridian) (Range) (Range) (Range) (Range) (Range) (Range) (Meridian) (State or Territory) (S	(INDICATE ABOVE BY CHECK MAI	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
Region of Section 7 (Twp) (Range) (Meridian) Agels Peak Dekota Sam Juan How Mexico (Field) (County or Subdivision) (State or Territory) to elevation of the derrick floor above sea level is Shad ft. DETAILS OF WORK to names of and expected depths to objective sandu; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, can ing points, and all other important proposed work) The state of the state with 275 sacks 65 gal mixed with 1-1/2 pounds The Plug or sack followed by 100 sacks neat coment. Tested water shut off with 300 of for 15 minutes with no pressure drop. With stage tool set at 2162', meented second stage with 150 sacks 15 gel. Tested water shut off with 300 of for 15 minutes and no indication of pressure drop. Resumed completion terations. The same of the stage to the same of the same o	y Gas Unit	Farmington, New Mexico October 31 , 19
Rev Mexico (Field) (County or Subdivision) (State or Territory) e elevation of the derrick floor above sea level is SALA ft. DETAILS OF WORK to names of and expected depths to objective sandus show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and all other important proposed work) real depth 6573'. 4-1/2" easing was set at 6569' and commend in two stages with 275 sacks 65 gel sixed with 1-1/2 pounds Taf Plug or sack followed by 100 sacks neat coment. Tested water shut off with 3000 of for 15 minutes with no pressure drop. With stage tool set at 2162', mented second stage with 150 sacks 45 gel. Tested water shut off with 300 of for 15 minutes and no indication of pressure drop. Resumed completion merations. understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. The manufacture of the best for the description of pressure drop. Resumed completion merations. The same of the derrick floor above sea level is SALA ft. The manufacture of the derrick floor above sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths of proposed casings; indicate mudding jobs, centing proposed works.	ll No. 1 is located 930 ft. fro	om. $\{S\}$ line and 1190 ft. from $\{E\}$ line of sec. 7
Rev Mexico (Field) (County or Subdivision) (State or Territory) e elevation of the derrick floor above sea level is SALA ft. DETAILS OF WORK to names of and expected depths to objective sandus show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and all other important proposed work) real depth 6573'. 4-1/2" easing was set at 6569' and commend in two stages with 275 sacks 65 gel sixed with 1-1/2 pounds Taf Plug or sack followed by 100 sacks neat coment. Tested water shut off with 3000 of for 15 minutes with no pressure drop. With stage tool set at 2162', mented second stage with 150 sacks 45 gel. Tested water shut off with 300 of for 15 minutes and no indication of pressure drop. Resumed completion merations. understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. The manufacture of the best for the description of pressure drop. Resumed completion merations. The same of the derrick floor above sea level is SALA ft. The manufacture of the derrick floor above sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths of proposed casings; indicate mudding jobs, centing points, and lengths of proposed casings; indicate mudding jobs, centing proposed works.	14 of Section 7 1-28-1	(Ranga)
ce elevation of the derrick floor above sea level is State of the DETAILS OF WORK to names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, can impoints, and all other important proposed work) that depth 6573'. 4-1/2" casing was set at 6569' and comented in two stage mented first stage with 275 sacks 6% gel mixed with 1-1/2 pounds Tuf Plug irr sack followed by 100 sacks neat coment. Tested water shut off with 3000 if for 15 minutes with no pressure drop. With stage tool set at 2162', mented second stage with 150 sacks 4% gel. Tested water shut off with 300 if for 15 minutes and no indication of pressure drop. Resumed completion wrations. understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Pan American Petrolaum Corporation liess Box 480		(Meridiali)
DETAILS OF WORK to names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and all other important proposed work) tal depth 6573'. 4-1/2" casking was set at 6569' and comented in two stages mented first stage with 275 sacks 6% gel mixed with 1-1/2 pounds fuf Plug or sack followed by 100 sacks neat coment. Tested water shut off with 3000 of for 15 minutes with no pressure drop. With stage tool set at 2162', mented second stage with 150 sacks 4% gel. Tested water shut off with 300 of for 15 minutes and no indication of pressure drop. Resumed completion wrations. understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. In pany Pan American Petroleum Corporation liess Box 480		
understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Inpany Pan American Petroleum Corporation Iress Box 480	te names of and expected depths to objective sands; show sing points, and all	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) was set at 6569° and comented in two stage
hress Box 480	te names of and expected depths to objective sands; show a ling points; and all tall depth 6573'. 4-1/2" casding a mented first stage with 275 sacks or sack followed by 100 sacks near it for 15 minutes with no pressuremented second stage with 150 sacks for 15 minutes and no indication	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) was set at 6569' and comented in two stages 65 gal mixed with 1-1/2 pounds Tuf Flug t coment. Tested water shut off with 3000 e drop. With stage tool set at 2162', ks 48 gal. Tested water shut off with 300
hress Box 480	te names of and expected depths to objective sands; show a ling points; and all tall depth 6573'. 4-1/2" casding a mented first stage with 275 sacks or sack followed by 100 sacks near it for 15 minutes with no pressuremented second stage with 150 sacks for 15 minutes and no indication	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) was set at 6569' and cemented in two stages 65 gel mixed with l-1/2 pounds fuf Plug t cement. Tested water shut off with 3000 e drop. With stage tool set at 2162', as 45 gel. Tested water shut off with 300 on of pressure drep. Resumed completion
iress	tenames of and expected depths to objective sands; show a ling points, and all teal depth 6573'. 4-1/2" casding a mented first stage with 275 sacks or sack followed by 100 sacks neat if for 15 minutes with no pressure mented second stage with 150 saci if for 15 minutes and no indication erations.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) was set at 6569' and cemented in two stages 6% gel mixed with 1-1/2 pounds Tuf Plug t sement. Tested water shut off with 3000 e drop. With stage tool set at 2162', as 4% gel. Tested water shut off with 300 on of pressure drop. Resumed completion
Parmingham House Handag	tenames of and expected depths to objective sands; show a ling points, and all tall depth 6573'. 4-1/2" casting washed first stage with 275 sacks or sack followed by 100 sacks near it for 15 minutes with no pressuremented second stage with 150 sacid for 15 minutes and no indication erations.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) was set at 6569' and comented in two stages 6% gel mixed with 1-1/2 pounds Tuf Plug t coment. Tested water shut off with 3000 e drop. With stage tool set at 2162', his 4% gel. Tested water shut off with 300 on of pressure drep. Resumed completion in writing by the Geological Survey before operations may be commenced.
By	tal depth 6573'. 4-1/2" casting vision and all tal depth 6573'. 4-1/2" casting vision for the stage with 275 sacks or sack followed by 100 sacks near for 15 minutes with no pressure mented second stage with 150 sacks for 15 minutes and no indication erations.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) was set at 6569' and comented in two stages 6% gal mixed with 1-1/2 pounds Tuf Plug t coment. Tested water shut off with 3000 e drop. With stage tool set at 2162', ks 4% gal. Tested water shut off with 300 on of pressure drep. Resumed completion in writing by the Geological Survey before operations may be commenced. The results of the commenced of the
	tal depth 6573'. 4-1/2" casing vinerated first stage with 275 sacks or sack followed by 100 sacks near for 15 minutes with no pressure mented second stage with 150 sacks for 15 minutes with no indication or 15 minutes and no indication erations. understand that this plan of work must receive approval in pany . Fan American Petroleum Condress	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) was set at 6569' and comented in two stages 6% gal mixed with 1-1/2 pounds Tuf Plug t coment. Tested water shut off with 3000 e drop. With stage tool set at 2162', ks 4% gal. Tested water shut off with 300 on of pressure drep. Resumed completion in writing by the Geological Survey before operations may be commenced. The results of the commenced of the