

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

SF-077111

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Storey "C"

9. WELL NO.

#3

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

Sec. 27, T-28-N, R-9-W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 1714, Durango, Colorado 81301

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1065' FNL 1850' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6817 GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐



## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Rig up spud 12/1/65. Drilled to 274. Set 10-3/4" 32.75# casing set at 274. Cemented w/200 sx. WOC. Drilled to 3186. Ran 98 joints 7-5/8" 24# casing set at 3183. Cemented w/385 sx. WOC. Drilled to 6441. Stuck drill pipe. Left 15 5" drill collars and 1 joint drill pipe in hole. Spotted 200 sx cement at 5197. WOC. Drilled cement to 5262. Set 300 sx cement plug at 5262. WOC. Drilled out cement to 5440. Spotted 3 each 20 bbl mill squeeze plugs on bottom. Spotted 150 sx cement at 5380 and 150 sx at 5292. WOC. Cleaned out to 6400. Drilled to TD 7694 on 1/7/66. Ran 241 joints 11.60# and 10.50# 4-1/2" casing set at 7694. Cemented w/150 bbls followed by 100 sx, 1st stage. 2nd stage w/100 sx thru collar at 5881. Now completing.



18. I hereby certify that the foregoing is true and correct

SIGNED

Harold C. Nichols

TITLE Senior Production Clerk

DATE January 13, 1966

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Distribution: 5 to USGS in Farmington, 1 to Continental, 1 to file.

\*See Instructions on Reverse Side