
Form	9-881	
(Feb.	. 1951)	



(SUBMIT IN TRIPLICATE)

Lease No. SF-077106 Unit W/1 Sec. 21

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL. NOTICE OF INTENTION TO CHANGE PLANS. NOTICE OF INTENTION TO TEST WATER SHUT-OFF. NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL. NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING.	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING. SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR. SUBSEQUENT REPORT OF ARANDOMMENT.
NOTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABOVE BY CHECK MA	ARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
Solle Lacken	August 3, , 19
/ell No is located	om. $\left\{ \begin{array}{c} N \text{ with and} \\ S \end{array} \right\}$ line and $\left\{ \begin{array}{c} 1 \text{ set. from } \\ W \end{array} \right\}$ line of sec. 21
(% Bec. and Bec. No.) (Twp.)	
(H Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
Undes, Dakete Sen Ju (Field) (Count	y or Subdivision) (State or Territory)
ne elevation of the de rifie That ab ove sea	
to elevation of the deliging upper apove sea	ievel is \$343 .
	AILS OF WORK
ate names of and expected depths to objective sands; show : ing points, and si	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement l other important proposed work)
• • • • • • • • • • • • • • • • • • • •	
	i other important proposed work)
Well spudded 7-38-68.	
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Coming was presented	t 9-5/8" 36# H-40 pesing at 259' with 190 ax
Well spudded 7-30-60. Drilled 12-1/4" hole to 250'; Se of easent. Casing was pressured to After easent set plug was drilled	t 9-5/8" 36# H-40 cesing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was pressured to After cement set plug was drilled	t 9-5/8" 36# H-40 cesing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was preserved that coment set plug was drilled	t 9-5/8" 36# H-40 pesing at 259' with 190 ax
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was preserved that coment set plug was drilled	t 9-5/8" 36# H-40 cesing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was pressured to After cement set plug was drilled	t 9-5/8" 36# H-40 cesing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure.
Well spudded 7-30-60. Drilled 12-1/4" hole to 250'; Se of easent. Casing was pressured to After easent set plug was drilled	t 9-5/8" 36# H-40 cesing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure.
Well spudded 7-30-60. Drilled 12-1/4" hole to 250'; Se of easent. Casing was pressured to After easent set plug was drilled	t 9-5/8" 36# H-40 cesing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was preserved for cement set plug was drilled for 30 minutes w/no appreciable d	t \$-5/8" 36# H-45 cesing at 259' with 190 ax to 500# fer 30 minute w/ne less in pressure. and rems on B.O.P. elesed and cesing pressure rep in pressure. Drilling resumed.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was preserved After cement set plug was drilled for 30 minutes w/no appreciable d	t 9-5/8" 36# H-40 cesing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was presented After cement set plug was drilled for 30 minutes w/no appreciable during the set of the	t \$-5/8" 36# H-45 casing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure. and runs on B.O.P. closed and casing pressure in pressure. Prilling resumed.
Well spudded 7-30-60. Drilled 12-1/4" hole to 250; Se of cement. Casing was presented After cement set ping was drilled for 30 minutes w/no approximable dunderstand that this plan of work must receive approval in mpany	t \$-5/8" 36# H-45 casing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure. and runs on B.O.P. closed and casing pressure in pressure. Prilling resumed.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was preserved. After cement set plug was drilled for 30 minutes w/no appreciable d	t \$-5/8" 36# H-45 casing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure. and runs on B.O.P. closed and casing pressure in pressure. Prilling resumed.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260'; Se of cement. Casing was preserved. After cement set plug was drilled for 30 minutes w/ne appreciable drilled for 30 minutes w/ne appreciable drilled for 30 minutes w/ne approval in mpany. Delhi-Tayler Oil Carpers fress. P. O. Dresser 1198	t \$-5/8" 36# H-45 casing at 259' with 190 ax to 500# for 30 minute w/ne less in pressure. and runs on B.O.P. closed and casing pressure in pressure. Prilling resumed.
Well spudded 7-30-60. Drilled 12-1/4" hole to 260; Se of cement. Casing was presented After cement set ping was drilled for 30 minutes w/no approximable dunderstand that this plan of work must receive approval in mpany	t \$-5/8" 36f H-45 cesing at 259" with 190 and to 500f for 30 mimate w/ne less in pressure, and rame on B.C.P. closed and casing pressure in pressure. Prilling resumed.