

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 077106

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

PO Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

990'S, 1850'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6345'GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lackey B

9. WELL NO.

12 (P&A)

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 21, T-28-N, R-9-W
NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Re-completion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Circulated hole, pumped 50 sk. cement below cement retainer which had been set 150' above Dakota perms. Left 15 sks. cement on top of retainer.

Perforated squeeze holes at 4234' (Mesa Verde), spotted 75 sk. cement plug, squeezed 50 sks. through perforations.

Spotted 20 sk. cement plug inside casing across Pictured Cliffs formation (Pictured Cliffs Formation was covered with cement on primary cement job.)

Perforated squeeze holes at 1645' (Ojo Alamo), spotted 50 sk. cement plug and squeezed 25 sks. through perforations.

Cut off and pulled 1500' of 5 1/2" casing, spotted 50 sk. cement plug over the casing stub.

Spotted 15 sk. cement plug at base of the surface pipe, 260'.

Installed Plug & Abandoned marker with 10 sk. cement surface plug.

(An additional subsequent report will be filed after location has been cleaned and revealed.)

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed F. H. WOOD

TITLE Petroleum Engineer

DATE March 15, 1972

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side