Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Poo]	Besin !	Dakota		·	Formation	D	akota		_County	San	Juan		
Initial XX Annual Special Date of Test 11-26-62													
Company Southern UnionProduction Co. Lease Angel Peak Well No. 23													
Unit C Sec. 11 Twp 28 North Rge. 11 West Purchaser Southern Union Gas Company													
Casing <u>L 1/2 Wt. 10.50 I.D. L.052</u> Set at 6198 Perf. 6208 To 6388													
Tubing 1 1/2 Wt. 2.90 I.D. 1.610 Set at 6195 Perf. 6190 To 6195													
Gas	Gas Pay: From 6208 To 6388 L 6190 xG 700 -GL 1333 Bar. Press. 12.0												
Proc	lucing Thru:	: Cas	sing		Tu	bing	XX	Type We	11 Sir	gle Ge	<u>-</u>	Dual	
Date	e of Complet	cion:_	11-19-	62	Packe	r <u>No</u>	211	keservo	ir Temp	J. OF			
	OBSERVED DATA												
Tested Through (Proper) (Choke) (Metan) Type Taps													
Flow Data							Tubing Data		Casing D	Casing Data Press. Temp.			
No.	(Prover) (Cho (Line) (Ori		ice)		s. Diff.			1			1		
SI	Size	Si	ize	psi	g h _w	o _F .		o _F ,	psig	F.	-	Hr.	
1.	211	 	3/4	1,3	9	680	5011		1565		1_	7 days 3 hours	
2. 3.		 											
<u>4.</u> 5.								 			-		
<u> </u>				ļ									
	Cooffici	l ont			Dwaggira	FLOW CAL	CULATION	is Gravity	Compre	88.	Rate	of Flow	
No.	Coefficient (24-Hour)		$\sqrt{h_{\mathbf{w}}p_{\mathbf{f}}}$		psia	ressure Flow		Factor Fg	Facto	tor		Q-MCYPD 15.025 psia	
1.	12-3650		V "wpf		list.	99		9258	1.0				
2.													
3. 4.													
5.													
PRESSURE CALCUIATIONS													
Gas]	Liquid Hydro	ocarbo	n Rati	0		cf/bbl.			fic Gravi				
Grav:	ity of Liqu	id Hyd:	rocarb	ons		deg.		Speci	fic Gravi	ty Flo			
Fc			(1-e ⁻⁸	'}		-	Pc_2	026	rc	4	104.7	
No.	$P_{\mathbf{W}}$	P	2 F	Q _o	$(F_cQ)^2$	2 (F	(cQ) ²	P _w 2	$P_c^2 - P_w^2$	1	al.	Pw Pc	
-	Pt (psia)	<u> </u>				(1	.–e ^{-s})	21,86.9	1617		Pw	P _C	
1. 2.								2400.9	1017.			1730	
3. 4.											<u> </u>		
5.													
	olute Poten							5		DEC	101	962	
	PANY				n Product						- 	14.	
ADDRESS P.O.Box 808, Farmington, New Mexico AGENT and TITLE Verse Bookhold, Jr. Engineer													
WITNESSED Verme Rockhold, Jr. Engineer COMPANY Southern Union Production Company REMARKS													
COM	FANI		N. C. CO.	LUNA	OB Procue	REI	ARKS						
ec: (3) New Mexico Oil Conservation Commission													
(1) Mr. Paul Clote (1) Mr. L. S. Muennink													
	(1) Mr. V	Val Ri	pper										
	(1) Mr. I (1) Mr. I	Bob Co	otto rliss										
	(1) File												

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- hw Differential meter pressure, inches water.
- FgI Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{nv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_{W} cannot be taken because of manner of completion or condition of well, then P_{W} must be calculated by adding the pressure drop due to friction within the flow string to P_{t} .