## UNITED STATES DEPARTMENT OF THE INTERIOR

		Dudget Duleau 140, 42-1/1424
	5.	LEASE
		SF-077084
	6.	IF INDIAN, ALLOTTEE OR TRIBE NAME
	7.	UNIT AGREEMENT NAME
nt —		FARM OR LEASE NAME
		Hubbell "A"
	9.	WELL NO.
		1-E
_,,	10.	FIELD OR WILDCAT NAME
		Basin Dakota
	11.	SEC., T., R., M., OR BLK. AND SURVEY OR
7		AREA
	1	Section 29, T28N, R10W
	12.	COUNTY OR PARISH 13. STATE
	1	San Juan New Mexico
 E,		API NO.
	15.	FLEVATIONS (SHOW DF. KDB. AND WD)

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
	Hubbell "A"
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR	1-E
Southland Royalty Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
P.O. Drawer 570, Farmington, N.M. 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	Section 29, T28N, R10W
AT SURFACE: 1820' FNL & 1850' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6069' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	**************************************
FRACTURE TREAT SHOOT OR ACIDIZE	
	.NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING 🗍	change on Form 9-330.)
MULTIPLE COMPLETE	
ABANDON* (other) Spud and Casing Report X	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertiner 10-10-80 Spudded 12-1/4" surface hole at 2:0 Total Depth of 238'. Ran 5 joints (set at 226'. Cemented with 120 sac per sack and 3% CaCl <sub>2</sub> . Plug down circulated to surface.	irectionally drilled, give subsurface locations and let to this work.)*  100 P.M. 10-10-80 and drilled to a 213') of 8-5/8", 24#, H-40 casing less of Class "B" with 1/4# gel flake
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED K.E. Filder TITLE Dist. Prod. I	Mgr. DATE October 13, 1980
(This space for Federal or State off	ice itse)
(This Space for redesal or State on	

\_\_\_\_\_ TITLE \_\_\_\_ \_\_\_\_\_ DATE \_\_\_\_\_ APPROVED BY CONDITIONS OF APPROVAL, IF ANY: