

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Southland Royalty Company	8. Farm or Lease Name Cain Com
3. Address of Operator P. O. Drawer 570, Farmington, New Mexico 87401	9. Well No. 12-E
4. Location of Well UNIT LETTER <u>O</u> , <u>820</u> FEET FROM THE <u>south</u> LINE AND <u>1840</u> FEET FROM THE <u>east</u> LINE, SECTION <u>16</u> TOWNSHIP <u>28N</u> RANGE <u>10W</u> NMPM.	10. Field and Pool or Wildcat Basin Dakota Undesignated Chacra
15. Elevation (Show whether DF, RT, GR, etc.) 5990' GR	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Spud and Casing Report</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-01-80 Spudded 12-1/4" surface hole at 8:00 P.M. 4-01-80 and drilled to a total depth of 205'. Ran 5 joints (188') of 8-5/8", 24#, K-55 casing set at 200'. Cemented with 140 sacks of Class "B" with 1/4# gel flake per sack and 3% CaCl<sub>2</sub>. Plug down at 4:00 A.M. 4-02-80. Cement circulated to surface.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE District Production Manager DATE April 2, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE ADMINISTRATOR DISTRICT # 3 DATE APR 3 1980

CONDITIONS OF APPROVAL, IF ANY: