

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 810' FSL & 1825' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Casing Report

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
SF-080781
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Cain
9. WELL NO.
11-E
10. FIELD OR WILDCAT NAME
Basin Dakota/Undesignated Gallup
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 15-T28N-R10W
12. COUNTY OR PARISH San Juan 13. STATE New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5935' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
- 3-08-80 Ran 159 joints (6658.92') of 5-1/2", 15.5#, K-55 casing set at 6670'. Stage Tools set at 2144' & 4778'. Cemented as follows:
- 1ST STAGE: with 165 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# gel flake per sack followed by 50 sacks of Class "B" Neat with 2% CaCl₂. Plug down at 2:45 P.M. 3-8-80.
- 2ND STAGE: with 320 sacks of Class "B" 50/50 Poz with 6% gel tailed in with 50 sacks of Class "B" Neat with 2% CaCl₂. Plug down at 7:45 P.M. 3-8-80.
- 3RD STAGE: with 200 sacks of Class "B" 50/50 Poz with 6% gel. Plug down at 10:30 P.M. 3-8-80.
- Top of Cement at 200'.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct


SIGNED [Signature] TITLE District Engineer DATE March 10, 1980

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE



ACCEPTED FOR RECORD

*See Instructions on Reverse Side

MAR 11 1980

FARMINGTON DISTRICT
BY McKuchera