UNITED STATES

5. LEASE	
SF 080724-A	!
6. IF INDIAN ALLOTTEE O	R TRIBE NAME

DEPARTMENT OF THE INTERIOR	SF 080724-A		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME		
	8. FARM OR LEASE NAME Zachry		
1. oil gas (X) other	9. WELL NO.		
2. NAME OF OPERATOR	18-E		
SUPRON ENERGY CORPORATION	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Basin Dakota - Wildcat Chacra		
P.O. Box 808, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
below.)	Sec. 11, T-28N, R-10W N.M.P.M.		
AT SURFACE: 960 ft./S ; 1455 ft./E line	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: Same as above	San Juan New Mexico		
AT TOTAL DEPTH: Same as above.	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5606 R.K.B.		
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Run and cement 4-1/2" casing	- - (NOTE: Report results of multiple completion or zone change on Form 9–330.)		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	irectionally drilled, give subsurface locations and		
 Drilled 7-7/8" hole with mud to T.D. of 64 on 3-1-80. 	450 ft. R.K.B. T.D. reached		
2. Ran 156 joints (6439 ft.) of 5-1/2", 15.50 6450 ft. R.K.B. with float collar at 6407			

- set @ 2986 ft. and 1310 ft. R.K.B.
- 3. Cemented first stage with 335 sx 50-50 POZ w/2% gel. Plug down at 7:30 a.m. 3-4-80. Cemented second stage w/500 sx Howco Lite and 50 sx of class "B". Plug down at 10:45 a.m. 3-4-80. Cemented third stage w/675 sx Howco Lite and 50 sx of class "B". Plug down at 2:15 p.m. 3-4-80. Cement circulated to surface on third stage.

Subsurface Safety Valve: Manu. and Type				Set @ Ft.
18. I hereby contify that the foregoing is	rue and correct			
SIGNED Kenneth E. Roddy	TITLE Production Supt.	DATE	March	18, 1980
	(This space for Federal or State office use)			MAKO COM.
APPROVED BY	TITLE	DATE	· 	OIL CON. COM.