

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
Tenneco Oil Company  
3. ADDRESS OF OPERATOR  
P. O. Box 3249, Englewood, CO 80155  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 800'FNL & 1840' FEL "B"  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:



5. LEASE  
SF 077107  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Michener  
9. WELL NO.  
1E  
10. FIELD OR WILDCAT NAME  
Basin Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 28, T28N R9W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6347' gr.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5/17/81. Drill to TD @ 7135'. Circ and cond hole. Short trip. POOH. Log w/ Gearhart-Owens to 7134'. RD and TIH w/drill pipe. Circ and cond. Laid down drill pipe.  
5/18/81. RU and run 179 jts. (7135') of 4½" 10.5 and 11.6# K-55 STC csg. Set @ 7135' w/DV @ 4000' KB. Circ and cond. Cmt 1st stage w/703sx Howco Lite and 1/4#/sk Flocele. Tail in w/100sx Class B. Plug down. Open DV circ 4 hrs. and WOC. No returns on 1st stage, partial returns when DV opened. Returns increased afterwards.  
5/19/81. Cmt 2nd stage w/1297sx Lite w/¼#/sk Flocele. Tail in w/50sx Class B w/2% CACL₂ and 1/4#/sk Flocele. Plug down 5/18/81. Circ cmt to liner top (surface). Nipple down. Set slips w/45000# cut off. Release rig 5/19/81.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carolyn Hutton TITLE Div. Asst. Amd. Mgr. DATE 5/27/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE MAILED FOR RECORD

NMOCC

\*See Instructions on Reverse Side

JUN 10 1981

BY Dean Elliott