

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Union Texas Petroleum Corp.
3. ADDRESS OF OPERATOR
P. O. Box 808, Farmington, N.M. 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: *1725 ft./S; 475 ft./E line*
AT TOP PROD. INTERVAL: *Same as above*
AT TOTAL DEPTH: *Same as above*
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>

SUBSEQUENT REPORT OF

X						
---	--	--	--	--	--	--

RECEIVED
1082

DEC 01 1982

U. S. GEOLOGICAL SURV
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

- | | |
|---|-------------------------|
| 5. LEASE
SF 080724-A | |
| 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | |
| 7. UNIT AGREEMENT NAME | |
| 8. FARM OR LEASE NAME
Zachry | |
| 9. WELL NO.
37 | |
| 10. FIELD OR WILDCAT NAME
Armenta Gallup Extension | |
| 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 11, T28N, R10W, N.M.P.M. | |
| 12. COUNTY OR PARISH
San Juan | 13. STATE
New Mexico |
| 14. API NO. | |
| 15. ELEVATIONS (SHOW DF, KDB, AND WD)
5727 R.K.B. | |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 14-3/4" surface hole at 8:00 P.M. 11/23/82.
2. Drilled 14-3/4" surface hole to total depth of 315 ft. R.K.B.
3. Ran 7 joints of 10-3/4", 40.50#, K-55 casing and set at 307 ft. R.K.B.
4. Cemented with 504 cu. ft. of Class "B" with 3% CaCl₂ and 1/4 lb. of Flocele per sack. Plug down at 3:30 A.M. 11/24/82. Cement circulated to the surface.
5. Waited on cement for 13 hours.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Area Prod. Supt DATE November 30, 1982
Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE _____

ACCEPTED FOR RECORD

***See Instructions on Reverse Side**

NMOCC

DEC 07 1982

FARMINGTON DISTRICT

צד