

(November 1983)
(formerly 9-330)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

6. LEASE DESIGNATION AND SERIAL NO.

SF-047039B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Kutz Federal Gas Com A

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Otero Chacra

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

SW/SW Sec8, T28N, R10W

12. COUNTY OR PARISH

13. STATE

San Juan

NM

19. ELEV. CASINGHEAD

5765' KB

5752' GR

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-TD

25. WAS DIRECTIONAL SURVEY MADE

Yes

27. WAS WELL CORED

No

1a. TYPE OF WELL:

OIL WELL ☐

GAS WELL ☒

DRY ☐

Other

b. TYPE OF COMPLETION:

NEW WELL ☒

WORK OVER ☐

DEEP-EN ☐

PLUG BACK ☐

DIFF. REVR ☐

Other

2. NAME OF OPERATOR

Amoco Production Co.

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, N M 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 840' FSL x 1000' FWL

At top prod. interval reported below Same

At total depth Same

RECEIVED

JUN 14 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

15. DATE SPUDDED

4-1-85

16. DATE T.D. REACHED

4-4-85

17. DATE COMPL. (Ready to prod.)

5-4-85

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

5765' KB

19. ELEV. CASINGHEAD

5752' GR

20. TOTAL DEPTH, MD & TVD

3100'

21. PLUG, BACK T.D., MD & TVD

3050'

22. IF MULTIPLE COMPL., HOW MANY*

single

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

2888'-2900' Chacra

26. TYPE ELECTRIC AND OTHER LOGS RUN

CDL-CNL-GR-CAL, DIL-GR-SP

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#, K55	305'	12-1/4"	354 cf Class B Ideal	
4-1/2"	24#, K55	3100'	7-7/8"	590 cf Class B Ideal and tailed in with 118 cf Class B Ideal	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2-3/8"	2884'	

31. PERFORATION RECORD (Interval, size and number)

2888'-2900', 2988'-3004', 4 jsfp, .50" in diameter, for a total of 112 holes.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
2888'-3004'	95,000 gal 70 quality foam and 160,000 # 12-20 brady sand.

33. PRODUCTION

DATE FIRST PRODUCTION

5-22-85

PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)

Flowing

WELL STATUS (Producing or shut-in)

Shut-in

DATE OF TEST

5-23-85

HOURS TESTED

3 hrs.

CHOKE SIZE

.75"

PROD'N. FOR TEST PERIOD

OIL—BBL.

GAS—MCF.

WATER—BBL.

GAS-OIL RATIO

441

FLOW, TUBING PRESS.

287 psig

CASING PRESSURE

528 psig

CALCULATED 24-HOUR RATE

OIL—BBL.

GAS—MCF.

WATER—BBL.

OIL GRAVITY-API (CORR.)

3525

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

Bryan Services

ACCEPTED FOR RECORD

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED B. Shaw

TITLE Adm. Supervisor

DATE 6-7-85

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or reports, or to furnish any information as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, to a tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	450	1650				
Fruitland	1650	1850				
Pictured Cliffs	1850	2466				
Chacra	2466	3100				