

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan  
Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 9-11-63  
Company PAN AMERICAN PETROLEUM CORP. Lease Gallegos Canyon Unit Well No. 137  
Unit \_\_\_\_\_ Sec. 36 Twp. 28N Rge. 13W Purchaser \_\_\_\_\_  
Casing 4-1/2 Wt. 10.5 I.D. \_\_\_\_\_ Set at 6100 Perf. 3978 To 3988  
Tubing 2-3/8 Wt. 4.7 I.D. 1.993 Set at 3961 Perf. Open Ended at 3961  
Gas Pay: From 3978 To 3988 L 3983 xG .70 est. -GL 4188 Bar.Press. 12  
Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well Single  
Single-Bradenhead-G. G. or G.O. Dual  
Date of Completion: 9-4-63 Packer None Reservoir Temp. \_\_\_\_\_

## OBSERVED DATA

Tested Through (Flow) (Choke) (None) Type Taps Flange

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI	<u>7 days</u>					<u>2023</u>		<u>2023</u>		
1.	<u>2 days</u>	<u>.750</u>	<u>720</u>			<u>623</u>		<u>1437</u>		<u>3 Hrs.</u>
2.										
3.										
4.										
5.										

## FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>11.3850</u>		<u>732</u>	<u>1.000</u>	<u>.9250</u>	<u>1.101</u>	<u>9223</u>
2.							
3.							
4.							
5.							

## PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)

Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 2035 P<sub>c</sub><sup>2</sup> 4,141,225

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> /P <sub>c</sub>
1.						<u>2,137,961</u>	<u>1,903,364</u>		<u>1.9190</u>
2.									
3.									
4.									
5.									

Absolute Potential: 16,034 MCFPD; n 0.75COMPANY PAN AMERICAN PETROLEUM CORPORATIONADDRESS Box 400, Farmington, New MexicoAGENT and TITLE F. L. Nabors, District Engineer, By: [Signature]

WITNESSED \_\_\_\_\_

COMPANY \_\_\_\_\_

REMARKS \_\_\_\_\_



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- $Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.
- $P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia
- $P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if  
flowing through casing.) psia
- $P_f$  = Meter pressure, psia.
- $h_w$  = Differential meter pressure, inches water.
- $F_g$  = Gravity correction factor.
- $F_t$  = Flowing temperature correction factor.
- $F_{pv}$  = Supercompressability factor.
- $n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .