Form 9-331 a (Feb. 1951)

U. P. Set Ceman

## (SUBMIT IN TRIPLICATE)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Santa Je	-
Lease No. 080844	
Unit	

Rhodes

NOTICE OF INTENTION TO CHANGE PLANS	JENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS.  NOTICE OF INTENTION TO TEST WATER SHUT-OFF.  NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF RIVERS OF INTENTION TO ABANDON WELL.  SW/A Sec. 31 28N 12W  (Twp.) (Range)  (Field) (County or Subdivision)  The elevation of the derrick floor above sea level is DETAILS OF W  (State names of and expected depths to objective sands; show sizes, weights, and ing points, and all other important points left full of coment. Fill up on casing to 470%. Pressure disposate of the control of the control of the control of the control of the casing set at 1831', coment joints left full of coment. Fill up on casing to 470%. Pressure disposate of the control of the cont	JENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.  NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF RESERVED IN THE CONTROL OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF RESERVED IN THE CONTROL OF RESERVED IN THE C	JENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL  (INDIGATE ABOVE BY CHECK MARK NATURE OF REAL PROPERTY OF THE NATION TO ABANDON WELL  (INDIGATE ABOVE BY CHECK MARK NATURE OF REAL PROPERTY OF THE NATION TO ABANDON WELL  (INDIGATE ABOVE BY CHECK MARK NATURE OF REAL PROPERTY OF THE NATION TO ABOVE OF THE NATION TO AB	IENT REPORT OF REDRILLING OR REPAIR
Rhodes Well No. 2 is located 990 ft. from S line  Rhodes (Range)  Rhodes (Range)  Rhodes (Range)  Rhodes (Range)  Rhodes (Range)  SW/4 Sec. 31 288 12W (Range)  (Field) (County or Subdivision)  The elevation of the derrick floor above sea level is DETAILS OF W  (State names of and expected depths to objective sands; show sizes, weights, and sing points, and all other important ing points, and all other important points left full of cement. Fill up on casing to 470%. Pressure disposed to 1734' with cable tools for water shut off. Hole tested of understand that this plan of work must receive approval in writing by the	
Rhodes Well No. 2 is located 990 ft. from S Inc.  SW/4 Sec. 31 288 12W  (Kange)  (Field) (County or Subdivision)  The elevation of the derrick floor above sea level is 605  DETAILS OF W  (State names of and expected depths to objective aands; show sizes, weights, an ing points, and all other important of 5/8" casing set at 1831', cement joints left full of cement. Fill up on casing to 470%. Pressure did 177/52  Drilled to 1734' with cable tools for water shut off. Hole tested of understand that this plan of work must receive approval in writing by the	JENT REPORT OF ABANDONMENT
Rhodes Well No. 2 is located 990 ft. from S Inc.  SW/4 Sec. 31 288 12W  (Kange)  (Field) (County or Subdivision)  The elevation of the derrick floor above sea level is 605  DETAILS OF W  (State names of and expected depths to objective annds; show sizes, weights, an ing points, and all other important points left full of cement. Fill up on casing to 470%. Pressure divided to 1734' with cable tools for water shut off. Hole tested of understand that this plan of work must receive approval in writing by the	SENTARY WELL HISTORY
Rhodes Well No. 2 is located 990 ft. from S income S inco	
Well No. 2 is located 990 ft. from S line  SW/4 Sec. 31 28N 12W  (Field) (County or Subdivision)  The elevation of the derrick floor above sea level is 605  DETAILS OF W  (State names of and expected depths to objective sands; show sizes, weights, an ing points, and all other important  9/7/52 TD 1831'  6 5/8" casing set at 1831', cement joints left full of cement. Fill up on casing to 470%. Pressure did 17/52  Drilled to 1734' with cable tools for water shut off. Hole tested of 1 understand that this plan of work must receive approval in writing by the	PORT, NOTICE, OR OTHER DATA)
Well No. 2 is located 990 ft. from S line  SW/4 Sec. 31 28N 12W  (Field) (County or Subdivision)  The elevation of the derrick floor above sea level is 605  DETAILS OF W  (State names of and expected depths to objective sands; show sizes, weights, an impoints, and all other importants of 5/8" casing set at 1831', cement joints left full of cement. Filliup on casing to 470%. Pressure dispositive sands to 470%. Pressure dispositive sands to 470%. Pressure dispositive sands of the full of cement. Filliup on casing to 470%. Pressure dispositive sands to 470%. Pressure dispositive sands of the full of cement. Filliup on casing to 470%. Pressure dispositive sands to 470%. Hole tested of the full of cement. Filliup on casing to 470%. Hole tested of the full of cement is for water shut off. Hole tested of the full of cement is for water shut off. Hole tested of the full of cement is for water shut off. Hole tested of the full of cement is for water shut off.	September 26 , 19_52
SW/4 Sec. 31 (Twp.) (Range)  (Field) (County or Subdivision)  The elevation of the derrick floor above sea level is 605  DETAILS OF W  (State names of and expected depths to objective sands; show sizes, weights, an ing points, and all other important of 5/8" casing set at 1831', cement joints left full of cement. Fill up on casing to 470%. Pressure disposal of the county of the	and 990 ft. from W line of sec. 31
(Field) (County or Subdivision)  The elevation of the derrick floor above sea level is	[ Y T ]
DETAILS OF W  (State names of and expected depths to objective sands; show sizes, weights, an ing points, and all other important  9/7/52 TD 1831'  6 5/8" casing set at 1831', cement joints left full of cement. Fill up on casing to 470%. Pressure displayed to 1734' with cable tools for water shut off. Hole tested of the content of the	(State or Territory)
DETAILS OF W (State names of and expected depths to objective sands; show sizes, weights, an ing points, and all other important  9/7/52 TD 1831'  6 5/8" casing set at 1831', cement joints left full of cement. Fill up on casing to 470#. Pressure displayed to 1734' with cable tools for water shut off. Hole tested of the content of the	
6 5/8" casing set at 1831', cement joints left full of cement. Fill up on casing to 470%. Pressure divided to 1734' with cable tools for water shut off. Hole tested of understand that this plan of work must receive approval in writing by the	
joints left full of cement. Fills up on casing to 470%. Pressure displayed to 1734 with cable tools for water shut off. Hole tested of a understand that this plan of work must receive approval in writing by the	
for water shut off. Hole tested of the standard of the standar	d hole with water and presented
	bailed hole dry and tested 3 hour
	Contraction of the second
Company Benson and Montin	Gellogical Survey before open tien may be commenced.
	1 60 10 35
Address 3153 West Main St.	
Farmington, N. M.	3 1/1
	By Albert R. Greer

OIL CONSERVATION ANTEC DISTE	RICT_OFFICE_
	DUTION
	NO. FURNISHED
Earna Fo	<u></u>
Otherstica Office State Land Office U. S. G. S.	
Transporter File	