COPY TO O. G. G.

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa Fe
Lease No.	078903-A
	I-Sec.844

Gallegos Canyon Unit


SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	X er	UBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	i 11	UBSEQUENT REPORT OF WATER SHOT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT		UBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPA	1 1	UBSEQUENT REPORT OF REDRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	1 1	UBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CA	ASINGSI	JPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		
(INDICATE ABOVE	BY CHECK MARK NATURE	OF REPORT, NOTICE, OR OTHER DATA)
		February 5 , 19_5
ell No is located 1	1980ft. from [N	line and 990 ft. from $\begin{cases} Ex \\ W \end{cases}$ line of sec. 34
SW/4 NW/4 Sec No.) 34	28N 12W (Range	N.M.P.M. (Meridian)
West Kuta	San Juan	New Mexico
(Fiala)	(County or Subdiv	vision) (State or Territory)
ing	points, and all other imp	ats, and lengths of proposed casings; indicate mudding jobs, ceme cortant proposed work)
Pictured Cliffs Sand test Surface Casing: 901 of 3	t. Estimated (10-3/4" OD 32.	F WORK ats, and lengths of proposed casings; indicate mudding jobs, comes contant proposed work) depth 15001.
Pictured Cliffs Sand test Surface Casing: 90' of 3	t. Estimated of 10-3/4" OD 32.7	F WORK Its, and lengths of proposed casings; indicate mudding jobs, cemes cortant proposed work) depth 1500%. 7# cemented to surface.
Pictured Cliffs Sand test Surface Casing: 90' of 3	t. Estimated of 10-3/4" OD 32.7	F WORK Its, and lengths of proposed casings; indicate mudding jobs, cemes contant proposed work) depth 1500%. 7# cemented to surface. 20#, cemented to surface.
Pictured Cliffs Sand test Surface Casing: 90' of 1 Production Casing: 1400 If commercial production shot with mytroglycerin.	t. Estimated of 10-3/4" OD 32.7 of 6-5/8" OD is indicated,	F WORK Its, and lengths of proposed casings; indicate mudding jobs, cemes contant proposed work) depth 1500%. 7# cemented to surface. 20#, cemented to surface.
Pictured Cliffs Sand test Surface Casing: 90' of 1 Production Casing: 1400 If commercial production shot with mytroglycerin.	t. Estimated of 10-3/4" OD 32.7 of 6-5/8" OD is indicated,	F WORK Its, and lengths of proposed casings; indicate mudding jobs, cemes contant proposed work) depth 1500%. 7# cemented to surface. 20#, cemented to surface. the producing section will
Pictured Cliffs Sand test Surface Casing: 90' of 1 Production Casing: 1400 If commercial production shot with mytroglycerin.	e sands; show sizes, weigh points, and all other imp t. Estimated (10-3/4" OD 32." of 6-5/8" OD is indicated,	the producing section will by the Geological Survey before operations may be commenced.
Pictured Cliffs Sand test Surface Casing: 90' of 1 Production Casing: 1400 If commercial production shot with nytroglycerin. I understand that this plan of work must recompany	e sands; show sizes, weigh points, and all other imp t. Estimated (10-3/4" OD 32.7 of 6-5/8" OD is indicated,	F WORK Its, and lengths of proposed casings; indicate mudding jobs, cemes contant proposed work) depth 1500%. 7# cemented to surface. 20#, cemented to surface. the producing section will

and the first of the second

At the state of

(1) 1977 克克 (1) 网络红野鱼家庭克



· 医乳头皮 · 网络阿拉拉斯 医皮肤无足术的 第三十年 注:

en de la composition La composition de la La composition de la

ing the control of th

And the second of the second o

and the second s

and the second of the second o

and the control of th

 $(-1)^{2} = (2\pi)^{2} + (2\pi)^{2}$

 \mathbf{r}_{i} , \mathbf{r}_{i}

the second of the second of

The second secon

 $\Phi_{\mathbf{p}}(\mathbf{r}) = \mathbf{p}_{\mathbf{p}}(\mathbf{r}) + \mathbf{p}_{\mathbf$