

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 07 078019
Unit L. H. Pipkin

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

L. H. Pipkin

Farmington, New Mexico - January 6, 1961

Well No. 7 is located 1785 ft. from N line and 790 ft. from E line of sec. 35

34 1/4 NW 1/4 Section 35
(1/4 Sec. and Sec. No.)

T-24-N
(Twp.)

R-11-E
(Range)

S. R. P. M.
(Meridian)

Basin Dakota Field
(Angels Peak Dakota Area)

San Juan
(County or Subdivision)


New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 5200 ft. (R.S.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth 6380' - Set 4-1/2" casing at 6380' with DV tool at 1907'. Cemented first stage with 275 sacks 6 percent gal cement with 1-1/2 pounds medium tuf plug per sack, followed by 100 sacks neat cement. Tested casing with 3000 psi for 15 minutes, which held with no indication of pressure drop. Cemented second stage with 150 sacks 6 percent gal cement. Tested casing with 3000 psi for 15 minutes which held with no indication of pressure drop. Drilled DV tool and cleaned out to 6334'. Displaced mud with water and left tubing in hole. Released rig December 28, 1960.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address P. O. Box 480

Farmington, New Mexico

Attn: L. O. Spear, Jr.

By R. M. Bauer, Jr.
Title Senior Petroleum Engineer