



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 077967
Unit Gallegos Canyon Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	Subsequent Report of Sand-Water Frac I

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico February 29, 1956

Well No. 72 is located 1730 ft. from N line and 1650 ft. from E line of sec. 36

NE 1/4 of Section 36 T-28-N R-13-W NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

West Kutz-Pictured Cliffs San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~drill hole~~ ground above sea level is 5817 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding job, cementing points, and all other important proposed work)

On January 25, 1956, this well was perforated with four jet shots per foot from 1440 feet to 1452 feet. Test before frac was 116 MCFPD.

Well was then sand-water fraced with 28,500 gallons water and 30,000 pounds sand. Formation broke at 2850 pounds. Average injection rate 41 BPM. Test after frac 3700 MCFPD.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company STANOLIND OIL & GAS COMPANY

Address P. O. BOX 487
FARMINGTON, NEW MEXICO

By L. O. Lewis
Title Field Superintendent