

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

NMSF 077967

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Gallegos Canyon Unit 158

9. API Well No.

3004507043

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

San Juan New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Pat Archuleta, Room 1205C

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

(303) 830-5217

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1545'FNL 1090'FW

Sec. 36 T 28N R 13W

Unit E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other Demand Letter 8/26/96

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRUSU 10/25/96.

Circulate hole clean, test casing to 500# for 15 min., held okay. Cement from CIBP AT 6030' to 5000' with 75 sxs of Class B cement. Cement from 2545-2245' with 23 sxs Class B cement. Cement from 1756-1106' with 50 sxs Class B cement. Cement from 1057-400' with 50 sxs Class B cement.

Perforated at 360', 220', 50' w/ 2 jsfp, .340 inch diameter, total 6 shots fired.

Attempted to pump cmt into perfs at 360' and 220', press to 1000# psi. Pumped 3.5bbls into perfs. TIH tbg and spot a cmt plug from 372' to 50' w/ 25 sxs cmt. Squeezed perfs at 50' with 221 sxs CI - B cement., circulate out perfs to surface, Pump 2.5 bbls cmt to Pit. cutoff well head, top off csg to surface.

RDSUMO 10/3096

Reference letter NMSF-077967 (WC) 3162.3-4 (070)

RECEIVED  
NOV 20 1996

OIL CON. DIV.  
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

*Pat Archuleta*

Title

Staff Assistant

Date

11-13-1996

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

APPROVED  
J. Duane W. Spencer  
NOV 19 1996

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

DISTRICT MANAGER