

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SF-078673

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Schlosser

9. WELL NO.

25

10. FIELD AND POOL, OR WILDCAT

Kutz Fruitland

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 27-T28N-R11W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL ☐ GAS ☒
WELL WELL OTHER

2. NAME OF OPERATOR

R & G DRILLING COMPANY

3. ADDRESS OF OPERATOR c/o Walsh Engr. & Prod. Corp.

P. O. Drawer 419 Farmington, New Mexico 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1850'FSL, 1850'FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

5617'D.F.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Repair Casing

X

(Note: Report results of multiple completion on Well
Completion or Reconnaissance Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).*

January 16, 1990

Locate two or more holes in 5-1/2" casing between 250' and 450'. Set retainer with bridge plug at 1250'. Cemented 2-3/8" tubing from surface to 1250' with 175 sacks (207 cu.ft.) Class "B" regular cement. (125 sacks, 148 cu.ft., circulated from bottom of tubing, 50 sacks, 59 cu.ft., pumped in annulus from surface).

Well will be produced through retainer and 2-3/8" tubing.

RECEIVED
FEB 05 1990
OIL CON. DIV.
DIST. 3

50 JAN 19 AM 11

FOR: R & G DRILLING COMPANY

18. I hereby certify that the foregoing is true and correct.

ORIGINAL SIGNED BY

SIGNED

EWELL N. WALSH

TITLE

Agent

DATE 1/18/90

Ewell N. Walsh

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side