Form 9-331 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land	Office	Sant	ta.	F	i <u>.</u>		ζ.		
Lease	No	SF ()78	90	4_				
Unit .	Gall	.ego	B. C	an	yo	n	þ	ŧ,	٦,
		i i Nas	1,		-	d	1.1	;	
	4								

	SUBSEQUENT REPORT OF WATER SHUT-OFF 8-5/8"	X
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF ALTERING CASING	1
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ABANDONMENT	1
NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING	l e e e e e e e e e e e e e e e e e e e	
•		
NOTICE OF INTENTION TO ABANDON WELL		
(INDICATE ABOVE BY CHECK MARK N	ATURE OF REPORT, NOTICE, OR OTHER DATA)	
Gallegos Canyon Unit	Fermington, New Mexico April 19 ,	19.
Vall No. 125 is located 1660 ft. from	$\begin{bmatrix} S \end{bmatrix}$ line and $\begin{bmatrix} 1650 \\ S \end{bmatrix}$ ft. from $\begin{bmatrix} M \\ W \end{bmatrix}$ line of sec.	24
VE/4 SW/4 Sec. 24 T-28-N I	L12-W N. M. P. M.	
V	New Mexico	
Indesignated Gallup San Juan (County or	Subdivision) (State or Territory)	
he elevation of the derrick floor above sea leve	el is 5843 ft.	
	S OF WORK	
	the second and the se	
On April 9, 1962 the above well was 8-5/8" easing was set at 214' and con	spudded and drilled to a depth of 21.	t a ent
On April 9, 1962 the above well was 8-5/8" casing was set at 214' and concentaining 2% calcium chloride. Came on cament tested casing with 400 psi	spudded and drilled to a depth of 21 mented with 180 sacks nest Incor cement was aircreated to surface. After	t a ent
On April 9, 1962 the above well was 8-5/8" casing was set at 214' and concentaining 2% calcium chloride. Came on cament tested casing with 400 psi	spudded and drilled to a depth of 21 mented with 180 sacks nest Incor cement was aircreated to surface. After	t a ent
On April 9, 1962 the above well was 8-5/8" casing was set at 214' and containing 2% calcium chloride. Came on cament tested casing with 160 psi and resumed drilling.	spudded and drilled to a depth of 21 mented with 180 sacks neat Incor cement was circulated to surface. After Test o.k. Reduced hole to 7-7/8"	t a ent
On April 9, 1962 the above well was 8-5/8" casing was set at 214' and concentaining 2% calcium chloride. Came on cament tested easing with 400 psi and resumed drilling.	spudded and drilled to a depth of 21 mented with 180 sacks neat Incor cement was circulated to surface. After Test o.k. Reduced hole to 7-7/8"	t a ent
On April 9, 1962 the above well was 8-5/8" casing was set at 214' and containing 25 calcium chloride. Came on coment tested casing with 160 psi and resumed drilling.	spudded and drilled to a depth of 21 mented with 180 sacks neat Incor cement was circulated to surface. After Test o.k. Reduced hole to 7-7/8" APR 2 1962 writing by the Geological Survey before operations may be confident.	i a nt
On April 9, 1962 the above well was 8-5/8° casing was set at 214' and containing 25 calcium chloride. Cam on cament tested casing with 400 psi and resumed drilling.	spudded and drilled to a depth of 21 mented with 180 sacks neat Incor coment was circulated to surface. After . Test o.k. Reduced hole to 7-7/8" APR 23 1962 writing by the Geological Survey before operations may be compared to the contract of the contr	t a ent
On April 9, 1962 the above well was 8-5/8" casing was set at 214' and concentaining 25 calcium chloride. Came on coment tested casing with 400 psi and resumed drilling. 1 understand that this plan of work must receive approval in the Company Pan American Petroleum Corp. Address Box 480	spudded and drilled to a depth of 21 mented with 180 sacks neat Incor cement was circulated to surface. After Test o.k. Reduced hole to 7-7/8" APR 2 1962 writing by the Geological Survey before operations may be confident.	t a ent
On April 9, 1962 the above well was 8-5/8" casing was set at 214' and concentaining 25 calcium chloride. Came on coment tested casing with 160 psi and resumed drilling. 1 understand that this plan of work must receive approval in the company Pan American Petroleum Corp.	spudded and drilled to a depth of 21 mented with 180 sacks neat Incor cement was circulated to surface. After . Test o.k. Reduced hole to 7-7/8" APR 23 1962 writing by the Geological Survey before operations may be configured by Original signed by	et at