


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **Santa Fe**
Lease No. **077076**
Unit **Jones**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	Subsequent Report of Treatment.....

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 23rd, 19 59

Well No. 1 is located 700 ft. from [N] line and 790 ft. from [E] line of sec. 17
SE 4 SE 4 Sec. 17 28N 13W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilcox San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6026 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7-9-59 TD 6358' RKB. Cleaned out to 6325'. Perforated 6304-18' with 4 jet shots per foot. Pressured up twice to 5000#. Formation would not break down. Pressured up twice to 5500#. Formation would not break down. Ran 2-3/8" tubing to 6322'. Spotted 500 gallons MCA. Pressured with acid truck to 3500#, broke to 2500#. Pulled tubing.

7-10-59 Sandfraced with 79,600 gallons water and 75,000# 20/40 sand, flushed with 20,000 gallons water. Breakdown pressure 1350#, average treating pressure 3850-3950#, maximum treating pressure 4000#, final pressure 3900#, shut-down pressure 1700#, average injection rate 59.5 barrels per minute.

(Continued)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Wilcox

Address _____

By _____ Page #1

Title _____

			X

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 577976
Unit Jones

Page 12

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Sandfrac Treatment</u>	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 23rd, 1959

Well No. _____ is located _____ ft. from $\begin{Bmatrix} N \\ S \end{Bmatrix}$ line and _____ ft. from $\begin{Bmatrix} E \\ W \end{Bmatrix}$ line of sec. _____

($\frac{1}{4}$ Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set Quiberson WNE magnesium bridge plug at 6270'.
Perforated 6234-44' with 4 jet shots per foot. Had
evidence of communication. Sandfraced with 30,000
gallons water and 80,000# 20/40 sand, flushed with
10,000 gallons water. Breakdown pressure 800#,
treating pressure 3800-4300#, average treating pressure
4100#, final pressure 4200#, shut-down pressure 1900#.
average injection rate 55 barrels per minute.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTIN-GREER DRILLING CORP.

Address 158 Petroleum Center Building

Farmington, New Mexico

By _____

Title Vice-President