



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 077976
Unit Jones

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Subsequent Report of Sandfrac Treatment</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 21st, 1959

Well No. 2 is located 1980 ft. from N line and 1980 ft. from E line of sec. 17
NW 4 SE 1/4 Sec. 17 28N 13W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6037 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

- 10-7-59 TD 5722' RKB. Cleaned out to 5701'. Perforated 5623-27' and 5660-76' with 4 jet shots per foot.
 10-9-59 Swabbed hole down. Ran tubing. Acidized with 250 gallons 15% HDA. Loaded hole with 100 barrels oil.
 10-12-59 Swabbed back load oil. Sandfraced with 53,424 gallons oil and 65,000# 20/40 sand, flushed with 4,200 gallons oil. Treating pressure 2500# average, 3000# maximum, final shut-down pressure 900#. Average injection rate 40 barrels per minute.
 10-13-59 Ran 2-3/8" OD KUE tubing to 5638' RKB. Commenced swabbing back load.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTIN-GREER DRILLING CORP.

Address 158 Petroleum Center Building

Farmington, New Mexico

By [Signature]
Title Vice-President