

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SHOWN IN TRIPLICATE
(Other instructions on reverse side)

Project No. 1004-11
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS ROOM

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. NAME OF OPERATOR HICKS OIL & GAS, INC.	3. ADDRESS OF OPERATOR P.O. DRAWER 3307 - FARMINGTON, NM 87499	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2040' FNL & 510' FEL	5. LEASE DESIGNATION AND SERIAL NO. SF 077968	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	7. UNIT AGREEMENT NAME SOUTHEAST CHA CHA	8. FARM OR LEASE NAME	9. WELL NO. 18	10. FIELD AND POOL, OR WILDCAT CHA CHA GALLUP	11. SEC., T., R., N., OR BLK. AND SURVEY OR AREA Sec. 16, T28N, R13W	12. COUNTY OR PARISH San Juan	13. STATE NM
14. PERMIT NO.	15. ELEVATIONS (Show whether BY, RT, GR, etc.)											

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12/08/88

- 1) Cleaned out to 4741'. Set cement retainer @4065' and spotted 370 sx Class B Cement from 4741' to 4015' inside and outside casing. Spotted mud from 4015' to 2686'.
- 2) Perforated @2686'. Set cement retainer @2636' and spotted 51 sx Class B Cement from 2686' to 2586' inside and outside casing. (Mesa Verde Top 2636') Spotted mud from 2586' to 1782'.
- 3) Perforated @1782'. Set cement retainer @1305' and spotted 264 sx Class B Cement from 1782' to 1255' inside and outside casing. (Pictured Cliff Top 1732', Fruitland Top 1305') Spotted mud from 1255' to 462'.

12/08/88

- 4) Perforated @462'. Pumped 202 sx Class B Cement and circulated cement to surface.
- 5) Erected Dry Hole Marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

JIM HICKS

TITLE

PRESIDENT

DATE 12/12/88

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

JAMES E. EDWARDS, JR.

*See Instructions on Reverse Side

NMOCC