

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SF-077976

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT ACQUISITION NAME
2. NAME OF OPERATOR	SOUTHEAST CHA CHA
3. ADDRESS OF OPERATOR	8. FIRM OR LEASE NAME
P.O. DRAWER 3307, FARMINGTON, NM 87499	9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)	10. FIELD AND POOL, OR VILLAGE
At surface	Cha Cha Gallup
660' FNL & 66' FWL	11. SEC. T. R. M. OR RAIL AND SURVEY OR AREA
	Sec. 17, T28N, R13W
14. ELEVATION	12. COUNTY OR PARISH
5977' GR	San Juan NM

OCT 18 1989
OIL CON. DIV.
DIST. 3

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRAC TURE TREAT ☐	MULTIPLE COMPLETE ☐	FRAC TURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT ☒
REPAIR WELL ☐	CHANGE PLANE ☐	(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. LOG AND LOGGING OF COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including a stated date of stoppage of work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and points pertinent to this work.)

09/19/89 Tuesday

MIRU. Pulled rods and pump. SDON

09/20/89 Wednesday

Released packer and pulled tubing. Started running tubing in hole. SDON

09/21/89 Thursday

Finished running tubing in hole and cleaned out to 5671'. Spotted 68.4 CF (58 sx) Class "B" Cement from 5671' - 5170' (Gallup Top @ 5220'). Spotted mud from 5170' - 2520'. T.T.O.H. and perforated @ 2520'. SDON

Approved as to plug and
Liability under bond to
surface owner.

See Attached

18. I her by certify that the foregoing is true and correct

SIGNED Jim Hicks TITLE President DATE 10/2/89

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

DATE 10/2/89

for Roy Ward

*See Instructions on Reverse Side

HICKS OIL & GAS, INC.
SOUTHEAST CHA CHA #11
Plug & Abandon
Page 2

09/22/89 Friday

T.T.I.H. and set cement retainer @ 2470' and spotted 60.2 CF (51 sx) Class "B" Cement from 2520' - 2420' inside and outside casing. (Mesa Verde Top @2470'). Spotted mud 2420' - 1590'. T.T.O.H. and perforated @1590'. T.T.I.H. and set cement retainer @ 1315' and spotted 192.3 CF (163 sx) Class "B" Cement from 1590' - 1265' inside and outside casing. (Pictured Cliff Top @ 1540' and Fruitland Top @ 1315'). Spotted mud from 1265' - 320'. T.T.O.H. and perforated @ 320'. Pumped 165.2 CF (140 sx) Class "B" Cement down casing and circulated cement out Bradenhead. SDOWE

09/25/89 Monday

Tagged top of surface plug @ 7.5' w/tubing. Erected dry hole marker.

JIM MORRIS of the Farmington BLM Office witnessed P & A Operations.