

9-331  
1973

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

JUL 12 1982

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR  
P.O. Box 3280 - Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 605' FNL & 535' FWL (NW NW NW)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO:                      | SUBSEQUENT REPORT OF:               |
|---|-------------------------------------|
| TEST WATER SHUT-OFF <input type="checkbox"/>  | <input type="checkbox"/>            |
| FRACTURE TREAT <input type="checkbox"/>       | <input type="checkbox"/>            |
| SHOOT OR ACIDIZE <input type="checkbox"/>     | <input type="checkbox"/>            |
| REPAIR WELL <input type="checkbox"/>          | <input type="checkbox"/>            |
| PULL OR ALTER CASING <input type="checkbox"/> | <input type="checkbox"/>            |
| MULTIPLE COMPLETE <input type="checkbox"/>    | <input type="checkbox"/>            |
| CHANGE ZONES <input type="checkbox"/>         | <input type="checkbox"/>            |
| ABANDON* <input type="checkbox"/>             | <input checked="" type="checkbox"/> |
| (other) <input type="checkbox"/>              |                                     |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Energy Reserves Group completed the following procedure to plug and abandon this well on 5-30-80.

1. With tbg. in the well, loaded hole w/drilling mud,
2. Spotted 10 sx Class "B" cement w/2% CaCl<sub>2</sub> from 1,200' - 1,100'.
3. Spotted 10 sx Class "B" cement w/2% CaCl<sub>2</sub> from 260' - 160'.
4. Spotted 5 sx Class "B" cement w/2% CaCl<sub>2</sub> from 50' - surface.
5. Installed dry hole marker.

Clean up and restoring of the location is planned for the near future.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bobby Patrick TITLE Production Engr-RMD DATE June 3, 1980

APPROVED BY [Signature] (This space for Federal or State office use)

APPROVED BY [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL JUL 8 1982

James F. Sims  
DISTRICT ENGINEER

\*See Instructions on Reverse Side

- LEASE  
SF-078106
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Gallegos Canyon Unit - Pictured Cliffs
8. FARM OR LEASE NAME
9. WELL NO.  
122
10. FIELD OR WILDCAT NAME  
West Kutz - Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
D Sec. 18-T28N-R12W
12. COUNTY OR PARISH  
San Juan
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
GRD 5,569'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)