

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

**SW-074807-A**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

**Gallegos Canyon Unit**

8. FARM OR LEASE NAME

9. WELL NO.

**100**

10. FIELD AND POOL, OR WILDCAT

**Totah Gallup**11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA**SW/4 NE/4 Section 12,  
T-28-N, R-13-W**

12. COUNTY OR PARISH

**San Juan**

13. STATE

**New Mexico**

1.

OIL ☒ GAS ☐  
WELL WELL OTHER

2. NAME OF OPERATOR

**PAN AMERICAN PETROLEUM CORPORATION**

3. ADDRESS OF OPERATOR

**P. O. BOX 489, Farmington, New Mexico**4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

**476' FRL. & 1980' FRL**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, SE, etc.)

**5609' (RDB)**

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Referring to our Form 9-331 of 4-1-66, the Gallegos Canyon Unit No. 100 was plugged and abandoned 4-6-66 as follows:

1. Spotted 40 sacks cement containing 6% Gel and 2% calcium chloride from FRL 5500' to about 5300' and squeezed.
2. Loaded hole with fluid and spotted 75 sacks cement containing 6% Gel and 2% calcium chloride from 4150' to 2850'.
3. Loaded hole with fluid and spotted 16 sacks cement from 1200' to 1100'.
4. Loaded hole with fluid and spotted 5 sacks cement (6% Gel and 2% calcium chloride) from surface to 50'.
5. Pumped 45 sacks cement (6% Gel and 2% calcium chloride) into 8-5/8" - 4-1/2" casing annulus.
6. Cut off wellhead, erected FMA marker, and cleaned up location.

18. I hereby certify that the foregoing is true and correct

SIGNED

**G. W. Eaton, Jr.**

TITLE

**Area Engineer**

DATE

**May 9, 1966**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.