

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-2013

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Tribal

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo

9. WELL NO.

2013-A-1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

11-28N-15W, 6th M

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5446 feet - DF

12. COUNTY OR PARISH

San Juan

13. STATE

New Mex

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

REPAIRING WELL

☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT* XXX

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11" hole was drilled to 177', 5 jts of 8-5/8" J-55 24# surface casing set at 155.03', cemented with 70 sx neat cement. Cement set 24 hrs. casing tested 1000# for 30 minutes. 6-3/4" hole was drilled to TD of 4705'. Induction-ES-Density Formation logs were run. Well was drillstem tested at 4595' to 4705', tool open 2 hours, strong blow gradually decreasing. Recovered 60' drilling mud, 60' slightly oil and gas cut watery drilling mud, 30' muddy salt water. FP 118-148#; 1 hr. ISIP 1800#; 1 hr FSIP 1486# Well was deemed to be non-productive, and plugged as follows in accordance with instructions from Mr. P. T. McGrath, USGS:
Plug #1: 4550-4705' with 37 sx cement; Plug #4: 350-450' with 25 sx.
Plug #2: 3200-3300' with 25 sx cement; Plug #5: 0- 30' with 10 sx.
Plug #3: 1250-1350' with 25 sx cement.

4" OD steel well marker was placed in top of surface casing. Plugging completed 5AM 8/23/64.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

4/27/67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

DATE

MAY 1 1967

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.

