

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

I-149-IND-8476

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Havajo Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Callegos Canyon Unit

9. WELL NO.

196

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 19, T28N, R12W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5887 RDB, 5875 GL

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)


Supplementary History

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 383. Cemented 8 5/8" 244 J-55 ST6C Casing at 383 with 250 sacks Type "A". Drilled to TD 6331. Set 4 1/2" 10.54 J-55 ST6C Casing at 6331 with stage tool at 4407. Cemented first stage with 400 sacks Type "C" with 6% gel with 2 lbs. Tuf plug per sack, followed by 100 sacks Type "C" Neat. Cemented second stage with 1000 sacks Type "C" with 6% gel with 2 lbs. Tuf plug per sack. Cleaned out to FSD 6297. Displaced hole with water containing .8% HCL with 2 1/2 lbs. FR-8 per 1000 gal. spotted 500 gal. 7 1/4% acid. Perforated 6223-45 with 4 shots/ft. Fraced with 43,410 gal. water treated as above with 40,000 lbs. 20-40 sand and 10,000 lbs. 10-20 sand. Breakdown pressure 1600. Treating pressure 3150 at 65 Hbls./Min. Set bridge plug at 6200. Perforated 6166-86 with 3 shots/ft. Did not frac. Cleaned out to FSD 6297. on 12/17/65 well tested 9,491 MCF/Day on 3/4" choke. TPF 741. CPT 1591.



18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED BY

SIGNED

D. I. Tollefson

D. I. TOLLEFSON

TITLE

Administrative Assistant

DATE

12/21/65

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.