

November 1983)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
(Other instructions on re-
verse side)

BLM Form No. 1004-1
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SF-078072

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

HICKS OIL & GAS, INC.

3. ADDRESS OF OPERATOR

P.O. DRAWER 3307 - FARMINGTON, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

381- FNL & 1930' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, XT, CR, etc.)

7. UNIT AGREEMENT NAME

SOUTHEAST CHA CHA

8. FARM OR LEASE NAME

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cha Cha Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 7, T28N, R13W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

12/7/88

- 1) Cleaned out to top of fish @3975' and spotted 51 sx Class B Cement from 3975' to 3875' inside and outside casing. Spotted mud from 3875' to 3110'.
- 2) Perforated @3110'. Set cement retainer @2410' and spotted 377 sx Class B Cement from 3110' to 2360' inside and outside casing. (Mesa Verde Top 3060', Chacra Top 2410'). Spotted mud from 2360' to 1520'.
- 3) Perforated @1520'. Set cement retainer @1355' and spotted 108 sx Class B Cement from 1520' to 1305'. (Pictured Cliff Top 1470', Fruitland Top 1355') Spotted mud from 1305' to 245'.
- 4) Perforated @245'. Pumped 80 sx Class B Cement and circulated cement to surface.
- 5) Erected dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

JIM HICKS

TITLE PRESIDENT

DATE 12/09/88

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

NM1004

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the
United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.