I

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Sente Po

Lease No. 57-079244-4

Unit Callegos Canyon Unit

STINDRY NOTICES AND DEPORTS ON

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING TO THE TOTAL
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OF BEND
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ARANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABOVE BY CHECK N	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
lleges Campun Unit	Farmington, New Nextee December 8 1059
-	, 19
ell No	rom $\{N\}$ line and 990 ft. from $\{E\}$ line of sec. 19
/4 of Section 19 T-28-N	R-12-W N.M.P.W.
(½ Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
onignated Dakota Sen Jes (Field)	Mew Mexico
(Cour	nty or Subdivision) (State or Territory)
ate names of and expected depths to objective sands; show ing points, and s ial depth 6230'. Row electric on ment first stage with 250 sacks 6 & followed by 160 sacks neet soon	FAILS OF WORK v sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) d somis logs. 7* easing was set at 6230* and if gel essent with 1-1/2 pounds 7sf-Plug per
ate names of and expected depths to objective sands; show ing points, and a sal depth 6230°. Rem electric amount first stage with 250 sacks on a followed by 100 sacks neat seming with 3000 per for 15 minutes when ted 2nd stage with 200 sacks on a sacks of minutes, which held with no indicates.	v sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) d semis logs. 7° easing was not at 6230° and 5 gel sement with 1-1/2 pounds Tuf-Plug per lent. Full returns throat first stage. Tested high held with no indication of pressure drop.
ate names of and expected depths to objective sands; show ing points, and a said depth 6230'. Rem electric am sent first stage with 250 sacks 600 k followed by 100 sacks neat sem by with 3000 per for 15 minutes when the said stage with 200 sacks 600 minutes, which held with no indicates, which held with no indicates. Plug back depth 6195'. Programmes of the sacks of	vizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) d semis logs. 7° easing was not at 6230° and 5 gel esment with 1-1/2 pounds Tuf-Plug per unt. Full returns threout first stage. Tested high held with no indication of pressure drop. 5 gel sement. Tested plug with 3000 per for eation of pressure drop. Drilled stage collar reparing for completion operations. DEC 1 0 1959
ate names of and expected depths to objective sands; show ing points, and a said depth 6230'. Rem electric am sent first stage with 250 sacks 600 k followed by 100 sacks neat sem by with 3000 per for 15 minutes when the said stage with 200 sacks 600 minutes, which held with no indicates, which held with no indicates. Plug back depth 6195'. Programmes of the sacks of	vizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) d semis logs. 7° easing was not at 6230° and 5 gel esment with 1-1/2 pounds Tuf-Plug per unt. Full returns threout first stage. Tested high held with no indication of pressure drop. 5 gel sement. Tested plug with 3000 per for eation of pressure drop. Drilled stage collar reparing for completion operations. DEC 1 0 1959
ate names of and expected depths to objective sands; show ing points, and a said depth 6230'. Rem electric am sent first stage with 250 sacks 600 k followed by 100 sacks neat sem by with 3000 per for 15 minutes when the said stage with 200 sacks 600 minutes, which held with no indicates, which held with no indicates. Plug back depth 6195'. Programmes of the sacks of	vizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) d semis logs. 7° easing was not at 6230° and gel esment with 1-1/2 pounds Tuf-Plug per unit. Full returns threout first stags. Tested high held with no indication of pressure drop. gel sement. Tested plug with 3000 per for eation of pressure drop. Drilled stage collar reparting for completion operations. DEC 1 0 1959 Oil CON. CON.
ate names of and expected depths to objective sands; show ing points, and a said depth 6230'. Rem electric an next first stage with 250 sacks for its followed by 160 sacks next sem by 160 sacks next sem by 160 sacks next sem with 3000 pei for 15 minutes with 3000 pei for 15 minutes with 3000 sacks frametes, which held with no indicates, which held with no indicates. Plug back depth 6195'. Provide the sacks of the sack	visces, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) d semis logs. 7° easing was not at 6230° and semis logs. 7° easing was not at 6230° and semis logs. 7° easing was not at 6230° and semis logs. 7° easing was not at 6230° and semis logs. 7° easing was not at 6230° and semistration of pressure throat first stage. Tested high held with no indication of pressure drop. See sement. Tested plug with 3000 pai for easing of pressure drop. Drilled stage collar reparing for completion operation. DEC 1 0 1959 Oil CON, COM, in writing by the Geological Survey before operation of pressure drop.
ate names of and expected depths to objective sands; show ing points, and a call depth 6230'. Rem electric an use first stage with 250 sacks for the followed by 160 sacks nest seem by with 3030 per for 15 minutes with 3	vizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) d semis logs. 7° easing was not at 6230° and gel esment with 1-1/2 pounds Tuf-Plug per unit. Full returns threout first stags. Tested high held with no indication of pressure drop. gel sement. Tested plug with 3000 per for eation of pressure drop. Drilled stage collar reparting for completion operations. DEC 1 0 1959 Oil CON. CON.