

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLSDo not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil
Well☒ Gas
Well☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325 - 1821

Location of Well (Footage, Sec., T., R., M., or Survey Description)

790' FNL & 1850' FWL
Sec. 36, T28N, R15W, NMPM

5. Lease Designation and Serial No.

14-20-603-2015

6. If Indian, Allotted or Tribe Name

Navajo Tribal

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pet Inc. #6

9. API Well No.

30 045 21C61

10. Field and Pool, or Exploratory Area

Basin Fruit and Coal/
Ojo Fruitland Sand PC

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
- ☐ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☒ Other Recomplete
- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Pump cement down 2-7/8" production casing to plug Pictured Cliffs/Fruitland Coal interval existing below external casing packer. Top of cement inside casing will be brought to at least 550'.
2. Pick up on 2-7/8" casing and pull in two or back off at some point in the hole. Spot cement plug wherever the casing parts or is backed off. If less than 50' of casing is recovered, the well will be plugged as previously approved.
3. Remove 5-1/2" surface casing, set at 20'. It may be possible to pull this casing given its shallow setting depth. If not, wash over and pull casing.
4. Drill 8-3/4" hole with mud until the top of the 2-7/8" casing is encountered.
5. At this point the hole will be sidetracked and a new hole section will be drilled.
6. Continue drilling with mud until near the Fruitland Coal top.
7. Run and cement 7" casing to surface. Casing will be set at approximately 600' (top of Fruitland Coal).
8. Drill out 7" casing with air through the Pictured Cliffs/Fruitland Coal interval.
9. Complete either open hole or set a slotted 4 1/2" liner on bottom to protect the open hole interval from falling in.
10. Should it be determined that this operation is encountering too many problems, this well will be plugged as previously approved.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander
John Alexander

Vice-president

Date

5/15/2001

(This space for Federal or State office use)

Approved by

Title

Date

5/19/01

Conditions of approval, if any: