STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

the vorm is not to be used for reporting pacter leekage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	Marathon Oi	1 Company	Lease _	Ohio B M	cCord	Well 1	
Location of Well: Unit	O Sec. 23	Twp. 28 -N	Rge	11-W	County	San Juan	
NAME OF RESERVOIR OR POOL			TYPE OF		METHOD OF PROD.	PROD. MEDIUM (Tog. or Cog.)	
Completion Fruitland			Gas		Flow	Casing	
Completes Pictured Cliffs			Gas		Flow	Tubing	
		PRE-FL	OW SHUT-IN F	RESSURE DAT	TA.		
Upper Hour, date shut-in		l -	Length of time shul-in		Stabilized? (Yes or No)		
Comptetten 10/18/92			5 Days		191 Yes		
Lower	10/10/00 2 D		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	SI proces, peop 180	3146	Stabilized? (Yes or No) Yes	
			FLOW TEST	NO. 1			
Commenced of Provinces	itej#			Zono producing (Upper or Lower			
TIME (hour, data)	LAPSED TIME SINCE*	PRES Upper Completion	SURE Lewer Completion	PROD. ZONE TEMP.		REMARKS	
10/18/92					Both Zone	Both Zones SI	
10/19/92		186	178		Both Zone	Both Zones SI	
10/20/92		188	179		Both Zone	Both Zones SI	
10/21/92		189	180		Both zone	Both zones SI	
10/22/92		190	178	ļ	Flowing 1	Flowing Lower Zone	
10/23/92		191	177		Flowing	Flowing Lower Zone	
Production rate of	•	Static	Spring =	250#	fice = .375	GOR	
Gas:					ter):		
				•	•		
MID-TEST SHUT-IN PRESSURE DATA Upper Mour. date shut-in Length of time shut-in St press. psig Stabilized? (Yes or No)							
Completion Lower Hear, date shut-in Length of time			si in	SI press. peig Stabilized? (Yes or Mc		Nzed? (Yes or No)	
Completton				<u> </u>			

FLOW TEST NO. 2

TIME (Pour, dote)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE			
		Upper Completion	Lower Completion	TEMP,	REMARKS		
. 					e de la companya de l		
Production rate	during test				•		
Oil:	ВОР	D based on	Bbls. in	Hours.	Grav GOR		
Gas:		MCF	PD: Tested thru	(Orifice or Meter):		
Remarks:					-		
I hereby certify t	that the informati	on herein contain	ed is true and con	mplete to the bes	t of my knowledge.		
Approved <u>DEC 17 1992</u>			_ 19 Operator MARATHON OIL COMPANY				
New Mexico C	Dil Conservation I	Division			. PRICE Thomas marine		
ByOrigina	al Signed by CHARI	TES CAROLINAM	т	ide ADVANC	ED ENGINEERING TECHNICIAN		
Tide DEPUTY	DEPUTY CH. 8 GAS INSPECTOR, DIST. 487 Date 12/03/92						

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage ten shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tens shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the rubing have been dimurbed. Tent shall also be taken at any time that communication is suspected or when requested by the Division.

nonced at (hour, date) 🕈 🕏

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shur-in for pressure stabilization. Both zones shall remain shur-in until the well-head pressure as each has stabilized, provided however, that they need not remain shur-in more than seven days.
- 4. For Flow Text No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the sumosphere due to the lack of a pspeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Ten No. 1. Providure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shur-in while the zone which was previously shur-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at faheen-minute intervals during the first hour thereof, and at houtly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least rwice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Parker Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).