Form 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATE® OTHER INTERIOR (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SF - 078828-A

(GEOL	.OGI	CAL	รบ	RVE	1

	SUNDRY NOTICES AND REPORTS ON WELLS
(Do not	use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

7.	UNIT	AGREEMEN	T NAME			
c	11 د	9008	Canyon	_	Ρ.	C

NAME OF OPERATOR

Energy Reserves Group, Inc

3. ADDRESS OF OPERATOR

OTHER

P. O. Box 3280, Casper, WY 82602

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

At surface

1400' FSL & 2500' FEL (SWNWSE)

9. WELL NO. #271

10. FIELD AND POOL, OR WILDCAT Kutz Pictured Cliffs

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

8. FARM OR LEASE NAME

Sec. 27-T28N-R12W

14. PERMIT NO.

16.

MELL GAS X

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Ground - 5,765'; K.B. - 5,774'

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
(Other)			ليبا	Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) * proposed work. I nent to this work.)

The above described well was spudded at 1:00 P.M., 12-11-76. Drilled 12-1/4" hole to 133'. Ran 3 jts - 124'(Net) - 8-5/8" O.D., 32#, K-55, R-3,ss, new casing set at 133' (K.B.). Cemented w/65 sx of regular cement w/3% CaCl2. Plug down at 6:00 P.M., 12-11-76. Good Returns. Nippled up and pressure tested BOPE to 400 psi. Held O.K. Drilled out $\sqrt[4]{7-7/8}$ " bit at 4:00 P.M., 12-12-76.



18. I hereby certify that the foregoing is true and correct SIGNED Once C Gillegue		
Kan C. G. W.	Operations Supt Drlg.	$_{\rm DATE}$ 12-14-76
SIGNED / Orece / July	ATTEMOPETATION DEPT.	
(This space for Federal or State office use)		
,		
APPROVED BY	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		