

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 42 R1454
5. LEASE DESIGNATION AND SERIAL NO.

SF-078863

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR R & G DRILLING COMPANY.		8. FARM OR LEASE NAME Krause
3. ADDRESS OF OPERATOR c/o Walsh Engineering & Prod. Corp. P.O. Box 254, Farmington, New Mexico 87401		9. WELL NO. 64
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1190' FSL, 1125' FEL		10. FIELD AND POOL, OR WILDCAT Kutz Fruitland
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29-T28N-R11W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5789' GR, 5799' DF, 5800' KB		12. COUNTY OR PARISH San Juan
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-31-77 Spud well.

12-31-77 Ran 3 jts. 8 5/8", 24.0 lb., K-55 casing (108). Set at 119' with 100 sacks Class "B" cement with 3% CaCl and 1/4 lb. Flocele per sack. Cement circulated. Test with 500 psig. Test OK

1-02-78 T.D. 1710'. Ran 52 jts., 4 1/2", 10.50 lb., K-55 casing (1663'). Set at 1674' with 136 sack 65/35 Pozmix with 12% gel and 6 1/4 lbs. Gilsonite per sack, 200 sacks 50/50 Pozmix "A" with 6 1/4 lbs. Gilsonite per sack. Cement circulated.

FOR: R & G Drilling Co.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ernest N. Walsh, P.E.

(This space for Federal or State office use)

President, Walsh Engineering
Production Corp.

DATE Feb. 3, 1978

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE