

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF- 078673

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Schlosser

9. WELL NO.

66

10. FIELD AND POOL, OR WILDCAT

Kutz Fruitland

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec27- T28N-R11W

N.M.:.M.

12. COUNTY OR PARISH 13. STATE

San Juan

NM

1. OIL ☐ GAS ☒  
WELL WELL OTHER

2. NAME OF OPERATOR

R & G Drilling Company

3. ADDRESS OF OPERATOR

c/o Walsh Engr. P.O. Box 254, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

560'FNL, 330'FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5655'GR, 5665'KB, 5666'DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-13-78 Spud well.

5-14-78 T.D. 140'

Ran 3 jts. 8-5/8", 24.0 lb, K-55 casing (122.00')  
set at 133.001 with 100 sacks Class "B" cement  
with 3 % Calcium Chloride and 6 1/4 lb. Flocele per  
sack. Cement circulated. Test with 500 psig.  
Test O.K.

5-16-78 T.D. 1668'

Ran 39 jts., 4 1/2", 10.50 lb, K-55 casing (1643.56')  
set at 1654.56' with 75 sacks 65/35 Pozmix (12% Gel)  
with 6 1/4 lbs. Gilsonite per sack followed by 350  
sacks 50/50 Pozmix with 6 1/4 lbs. Gilsonite per  
sack. Cement circulated.

RECEIVED

For: R & G Drilling Company

18. I hereby certify that the foregoing is true and correct

President, Walsh Engr.

SIGNED

Ewell N. Walsh, P.E.

TITLE & Production Corp.

DATE 6-6-78

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: