

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well
2. NAME OF OPERATOR
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR
P.O. Box 3280, Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2480' FSL & 2360' FWL (NE/SW)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

☐ TEST WATER SHUT-OFF
☐ FRACTURE TREAT
☐ SHOOT OR ACIDIZE
☐ REPAIR WELL
☐ PULL OR ALTER CASING
☐ MULTIPLE COMPLETE
☐ CHANGE ZONES
☐ ABANDON*
(other) Well History

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
SF-078904-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Gallegos Canyon Unit
8. FARM OR LEASE NAME
Gallegos Canyon Unit
9. WELL NO.
281
10. FIELD OR WILDCAT NAME
W. Kutz - Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 25-T28N-R12W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
G.L. 5,867' KB 5,877'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded @ 8:30 P.M. 12-16-79.

Drilled 12-1/4" hole to 133' K.B. Ran 3 jts. 8-5/8" O.D. 20#, MU-46, 8Rth, ST&C R-3 new casing set @ 131' K.B. Cemented w/100 sx Class "B" w/3% CaCl₂ and 1/4# Flocele/sx. Good cement returns.

Nipple up and pressure tested BOPE to 800 psi - held o.k.

Drilled 6-3/4" hole to 1,929' and ran logs.

Ran 49 jts. 4-1/2" O.D. 9,5#, K-55, R-3, SS, ST&C new casing set @ 1,928' (K.B.)

Cemented w/400 sx 50-50 Pozmix w/1/4# Flocele/sk. Plug down @ 6:45 P.M. 12-20-79.

Good circulation throughout - circulate cement water.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. D. Thomas TITLE Drilling Foreman DATE 12-27-79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NMOCC

*See Instructions on Reverse Side

JAN 07 '80

BY _____

2019

2020

2021