

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other2. NAME OF OPERATOR
Energy Reserves Group, Inc.3. ADDRESS OF OPERATOR
P.O. Box 3280, Casper, Wyoming 826024. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1520' FSL & 1530' FWL (NW SE)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) Well History ☒

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☐☒5. LEASE
SF 078106

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Gallegos Canyon Unit8. FARM OR LEASE NAME
Gallegos Canyon Unit9. WELL NO.
29010. FIELD OR WILDCAT NAME
West Kutz-Pictured Cliffs11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 15-T28N-R12W12. COUNTY OR PARISH
San Juan13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
G.L. 5660' - KB - 5670'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded @ 12:45 PM 12-9-79. Drilled 12-1/4" hole to 132' KB. Ran 3 jts. 8-5/8" 20#, MU46, R-3, 8Rth, new casing set @ 131' KB.

Cemented w/100 sx Class "B" cement w/3% CaCl₂ & 1/4# Celloflake/sk. Plug down @ 6:30 AM 12-9-79. Good cement returns.

Drilled 6-3/4" hole to 1741' KB and ran logs.

Ran 44 jts. of 4-1/2" 9.5#, K-55, 8Rth, R-3 new casing set @ 1739' KB. Cemented w/325 sx 50-50 Pozmix w/1/4# Celloflake/sk. Plug down @ 10:00 PM 12-12-79. Circulated out est. 40 sx good cement.

12-13-79 - W.O.C. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Drlg. Foreman DATE 12-13-79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.