

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR  
P.O. Box 3280, Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1080' FNL & 1720' FEL (NW/NE)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) Well History

## SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

X

5. LEASE  
SF-078106
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Gallegos Canyon Unit
8. FARM OR LEASE NAME  
Gallegos Canyon Unit
9. WELL NO.  
297
10. FIELD OR WILDCAT NAME  
West Kutz Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 15-T28N-R12W
12. COUNTY OR PARISH  
San Juan
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
G.L. 5,585' KB 5,595'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The above referenced well was spudded @ 7:00 P.M. 1-3-80.  
Drilled 12-1/4" hole to 131' KB and set 3 jts 8-5/8", 19.66#, MU46, 8Rth, R-3 ST&C new casing @ 131' KB. Cemented w/100 sx Class "B" cement w/3% CaCl<sub>2</sub> & 1/4# Flocele/sk Plug down @ 8:00 A.M. 1-4-80. Good cement returns.  
Nipple up and pressure tested. BOPE to 800 psi - Held o.k.  
Drilled 6-3/4" hole to 1,697' KB & ran logs.  
Set 51 jts of 4-1/2", 10.5#, CW55, R-2, SS, ST&C new casing @ 1,668' KB. Cemented w/325 sx 50-50 Pozmix & cement w/2% Gel + 1/4# Flocele/sk. Plug down @ 1:00 P.M. 1-7-80. Good cement returns. Cement circulated.  
1-8-80 - W.O.C. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type

Set @ SE Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Drilling Foreman DATE 1-8-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.