

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
Energy Reserves Group, Inc.

3. ADDRESS OF OPERATOR  
P.O. Box 3280, Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1080' FNL & 1720' FEL (NW/NE)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Well History			X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The above referenced well was spudded @ 7:00 P.M. 1-3-80.  
Drilled 12-1/4" hole to 131' KB and set 3 jts 8-5/8", 19.66#, MU46, 8Rth, R-3 ST&C new casing @ 131' KB. Cemented w/100 sx Class "B" cement w/3% CaCl<sub>2</sub> & 1/4# Flocele/s Plug down @ 8:00 A.M. 1-4-80. Good cement returns.  
Nipple up and pressure tested. BOPE to 800 psi - Held o.k.  
Drilled 6-3/4" hole to 1,697' KB & ran logs.  
Set 51 jts of 4-1/2", 10.5#, CW55, R-2, SS, ST&C new casing @ 1,668' KB. Cemented w/325 sx 50-50 Pozmix & cement w/2% Gel + 1/4# Flocele/sk. Plug down @ 1:00 P.M. 1-7-80. Good cement returns. Cement circulated.  
1-8-80 - W.O.C. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_

TITLE Drilling Foreman DATE 1-8-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

OPERATOR

BLM

MOCC

\*See Instructions on Reverse Side