

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR  
P.O. Box 3280, Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FNL & 1570' FWL (NE/NW)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Well History ☒

## SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED  
JAN 1 1980  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The above referenced well was spudded @ 11:30 A.M. 12-21-79. Drilled 12-1/4" hole to 133' K.B. Ran 3 jts. 8-5/8" 20# MU46, R-3 8Rth ST&C new casing. Set @ 131' KB. Cemented w/100 sx Class "B" cement w/3% CaCl<sub>2</sub> + 1/4# Flocele/sk. Plug down @ 6:30 P.M. 12-21-79. Good cement returns.  
Nipped up and tested BOPE to 800 psi. - Held o.k.  
Drilled 6-3/4" hole to 1,840' K.B. and ran logs.  
Ran 46 jts. 4-1/2", 9.5#, K-55, R-3, 8Rth, ST&C new casing set @ 1,829' K.B. Cemented w/400 sx 50-50 Pozmix w/2% Gel + 1/4# Flocele/sk. Plug down @ 6:45 P.M. 12-29-79. Good returns throughout.  
Ran temperature survey - top of cement @ 200' +/-  
12-31-79 - W.O.C. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Drilling Foreman DATE 1-2-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:ACCEPTED  
JAN 17 1980  
FARMINGTON, N. M.