

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR ARCO Oil and Gas Company
Division of Atlantic Richfield Company
3. ADDRESS OF OPERATOR
P. O. Box 5540, Denver, Colorado 80217
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 985' FSL & 1530' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Approx the

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) N.O. setting production casing ☐

5. LEASE SF 078673	6. IF INDIAN, ALLOTTEE OR TRIBE NAME ---
7. UNIT AGREEMENT NAME ---	8. FARM OR LEASE NAME Schlosser
9. WELL NO.	10. FIELD OR WILDCAT NAME Basin Dakota
11. SEC., T., R., M. OR BLK. AND SURVY OR AREA 27-38N-11W	12. COUNTY OR PARISH San Juan
13. STATE New Mexico	14. API NO. 30-045-24120
15. ELEVATIONS (SHOW DF, XDB, AND WD) 5651	

(NOTE: Report results of multiple completion change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 6230' and logged. Ran 149 jts (6246.95') 4-1/2" casing. GS set @ 6299', FC @ 6185' with DV tool @ 1940'. Cemented in stages. First stage - circled mud 1-1/2 hours; pumped 500 BW, 450 sxs Halliburton lite with 10# gilsonite/sx, 3/4" CFR-2 & 2% gel & 3/4" CFR-2. P.D. @ 2:30 am 4-10-80. Second stage - 500 gals mud flush, 10 BW, 200 sxs Halliburton lite, 3/4" CFR-2, 2% CaCl₂ & 280 sxs 50/50 poz mix, 2% gel, 3/4" CFR-2 & 2% CaCl₂. P.D. @ 6:12 am 4-10-80. Had good returns throughout entire run.

Released rig @ 9:00 am 4-10-80.

Waiting on completion.

Subsurface Safety Valve: Manu. and Type _____


18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Walther, Jr. TITLE Operations Manager DATE _____

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:



ACCEPTED FOR RECORD

APR 17 1980

FARMINGTON DISTRICT

NMOCC

BY [Signature]