

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR ARCO Oil and Gas Company  
Division of Atlantic Richfield Company  
3. ADDRESS OF OPERATOR  
P. O. Box 5540, Denver, Colorado 80217  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17  
below.)  
AT SURFACE: 1595' FNL & 2170' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Approx the same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☐  
N.O. perf, frac & acidize  
(other)

5. LEASE  
SF 078863  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
---  
7. UNIT AGREEMENT NAME  
---  
8. FARM OR LEASE NAME  
Krause WN Federal  
9. WELL NO.  
8E  
10. FIELD OR WILDCAT NAME  
Basin Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR  
AREA  
29-28N-11W  
12. COUNTY OR PARISH 13. STATE  
San Juan New Mexico  
14. API NO.  
30-045-24123  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5750' GL

(NOTE: Report results of multiple completion or zone  
change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,  
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and  
measured and true vertical depths for all markers and zones pertinent to this work.)\*


MI & RU. Spotted 100 gals 15% MSR @ 6246'. Perf'd Dakota @ 6151', 53, 55,  
56, 58, 6208, 10, 14, 17, 19, 21, 23, 26, 28, 30, 32, 35, 37'-18 holes. Spotted 100 gals  
acid @ 6006'. Treated with 1500 gals 15% MSR. Frac'd with 62,000 gals  
2% KCL water, 216,000# 20/40 mesh sand, 11,000 gals pad & 4,000 gals flush.



ACCEPTED FOR RECORD

JUL 3 1980

FARMINGTON DISTRICT  
BY *[Signature]*



Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED *W.A. Walther, Jr.* TITLE Operations Manager DATE 6-27-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: