

5-USGS (Farmington) 1-Mountain Fuel (SLC) 1-Mountain Fuel (FMG) 1-File

Form Approved  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

Dugan Production Corp.

3. ADDRESS OF OPERATOR

Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
790' FSL - 790' FEL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☒ Acidize  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

MAR 24 1982

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
NM 25455

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Aunt America

9. WELL NO.  
#1

10. FIELD OR WILDCAT NAME  
WAW FR PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 32 T28N R13W

12. COUNTY OR PARISH  
San Juan

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5890' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-24-82 Move in and rig up Hinson Service Co. Initial fluid level 450'. Swabbed well down. Rigged up Allied Services. Acidized well using 250 gal 15% hydrochloric (HCL) acid. Breakdown pressure 1600#, pumping rate 3 bbl/min at 900#. Finished acid pumping 4 bbl/min at 950#. Displaced with 7 bbl of water. Instant shot in pressure 550#. Swabbed well. NO indication of gas or oil. Waited 15 min. Fluid level 150' from bottom. Swabbed well down. Waited 10 min. Fluid level 75' from bottom. Rigged down and shut in well.

Subsurface Safety Valve: Make and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Thomas A. Dugan TITLE Petroleum Engineer DATE 3-26-82

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

ACCEPTED FOR RECORD

MAR 30 1982

NMOCC