

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR ARCO Oil and Gas Company
Division of Atlantic Richfield Company

3. ADDRESS OF OPERATOR
P. O. Box 5540, Denver, Colorado 80217

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1520' FNL & 1650' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Approx the same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☐
☐
☐
☐
☐
☐

(other) N.O. setting production casing

5. LEASE

SF 078673

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Schlosser WN Federal

9. WELL NO.

5E

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

34-28N-11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

30-045-24425

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5715' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 6280' & logged. Drilled another 30' and ran 148 jts 4-1/2", 10.5#, K-55 (6329.96') and set @ 6310'. Pmped 10 bbls mud flush. Cemented 1st stage with 315 sx 65/35 poz mix, 14% gel, 12-1/2# gilsonite/sx followed with 290 sx 50/50 poz mix, 2% gel, 3/4% CFR-2. P.D. @ 10:00 pm 8-7-80. Opened DV & circl for 3-1/2 hrs. Pmped 10 bbls mud flush, cmted with 390 sxs 65/35 poz mix with 14% gel, 12-1/2% gilsonite/sx. Cmt circl as plug bumped. P.D. @ 3:00 am 8-8-80.

Released rig @ 5:00 am 8-8-80.

Waiting on completion.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Walther, Jr. TITLE Operations Manager DATE 8-14-80

(This space for Federal or State office use)

APPROVED BY FOR DEPT. TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

AUG 20 1980

FARMINGTON DISTRICT

BY W. A. Walther, Jr.

*See Instructions on Reverse Side