

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
*SUPRON ENERGY CORPORATION*

3. ADDRESS OF OPERATOR  
*P.O. Box 808, Farmington, New Mexico 87401*

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: *990 ft./N ; 1650 ft./W line*  
AT TOP PROD. INTERVAL: *Same as above*  
AT TOTAL DEPTH: *Same as above*

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

*SF 047017-B*

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

*Angel Peak "B"*

9. WELL NO.

*27-E*

10. FIELD OR WILDCAT NAME

*Basin Dakota*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

*Sec. 25, T-28N, R-11W, N.M.P.M.*

12. COUNTY OR PARISH

*San Juan*

13. STATE


*New Mexico*

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

*5820 R.K.B.*

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- Spudded 12 1/4" surface hole at 11:45 p.m. 12-27-80.*
- Drilled 12 1/4" surface hole to total depth of 294 ft. R.K.B.*
- Ran 6 joints of 8-5/8", 24.00#, H-40 casing and set at 290 ft. R.K.B.*
- Cemented with 275 sacks of class "B" with 3% calcium chloride. Plug down at 7:00 a.m. 12-28-80. Cement circulated to surface.*
- Waited on cement for 12 hours.*
- Pressure-tested casing to 1000 PSI for 15 minutes, held OK.*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Kenneth E. Roddy* TITLE *Production Supt.* DATE *December 30, 1980*  
*Kenneth E. Roddy*

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITION OF APPROVAL IF ANY

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

JAN 07 1981

FARMINGTON DISTRICT  
*BLN*

\*See Instructions on Reverse Side

NMOCC