

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR
P.O. Box 3280 - Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1,000' FSL & 810' FEL (SE/SE)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Well History ☒

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☒

5. LEASE
SF-078109
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Gallegos Canyon Unit
8. FARM OR LEASE NAME
9. WELL NO.
308
10. FIELD OR WILDCAT NAME
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
P-7-28N-12W
West Kutz Pictured Cliffs
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
G.L. 5,605'; K.B. 5,607'

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded @ 11:00 AM 3-22-81.

Drld 9-7/8" hole to 125'. Ran 3 jts 7" O.D., 17#, H-40, R-3, ST&C new casing set @ 123;. Cemented w/60 sx of Class "G" cement w/2% CaCl₂ & 1/4# Celloflake. Plug down @ 4:00 PM 3-22-81. Good cement returns.

N.U. & pressure tested BOPE to 500 psi--held o.k.

Drld 6-1/4" hole to 1,578' & ran lggs.

Ran 40 jts 4-1/2" O.D., 10.5#, K-55, R-3, ST&C new casing set @ 1,574'. Cemented w/225 sx of 50-50 Pozmix w/2% Gel & 1/4# Celloflake & 0.5% D-33. Plug down @ 11:45 PM 3-24-81. Good cement returns.

3-2581 - W.O.C.T.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth Gillespie TITLE Drllg Supt - RMD DATE 3-25-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

MOCC

