UNITED STATES DEPARTMENT OF THE INTERIOR

| | 546BCF 55168B 110. 42-R1424 |
|--------|--|
| | 5. LEASE SF78106 |
| | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| | |
| | 7. UNIT AGREEMENT NAME |
| ent | Gallegos Canyon Unit |
| | 8. FARM OR LEASE NAME |
| | 9. WELL NO. 314 |
| | 10. FIELD OR WILDCAT NAME |
| | West Kutz Pictured Cliffs |
| 17 | 11. SEC., T., R., M., OR BLK. AND SURVEY OF |
| 1, | Sec. 17-T28N-R12W |
| | 12. COUNTY OR PARISH 13. STATE San Juan New Mexico |
| | 14. API NO. |
| E, | |

| GEOLOGICAL SURVEY | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | |
|--|--|--|
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) | 7. UNIT AGREEMENT NAME Gallegos Canyon Unit 8. FARM OR LEASE NAME | |
| 1. oil gas well other | 9. WELL NO. 314 | |
| 2. NAME OF OPERATOR Energy Reserves Group, Inc. 3. ADDRESS OF OPERATOR P.O. Box 3280 - Casper, Wyoming 82602 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: AT TOP PROD. INTERVAL: | 10. FIELD OR WILDCAT NAME West Kutz Pictured Cliffs 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 17-T28N-R12W 12. COUNTY OR PARISH San Juan 13. STATE New Mexico | |
| AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA | 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) G.L. 5,648'; K.B. 5,650' | |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Recementing x CSG 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent | (NOTE: Report results of multiple completion or zone change on Form 9–330.) all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and | |
| Energy Reserves Group, Inc., as operator of the perforate the 4-1/2" production casing @ \pm 1, @ \pm 1,200' and recement the 4-1/2" production of 50-50 Pozmix cement. | he subject well proposes to 250', set a cement retainer | |
| Subsurface Safety Valve: Manu. and Type | Ft. 19 | |
| SIGNED A FITTLE Prod. Engr- R | 7:750 20 2004 | |

- DISTRICT ENGINEER