

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
Amoco Production Company  
3. ADDRESS OF OPERATOR  
501 Airport Drive, Farmington, NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1550' FNL x 800' FEL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Spud and Set Casing

SUBSEQUENT REPORT OF:


☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

OCT 30 1981

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of completion or zone change on Form 9-330)



5. LEASE  
SF-047019B  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
Gallegos Canyon Unit  
8. FARM OR LEASE NAME  
9. WELL NO.  
167E  
10. FIELD OR WILDCAT NAME  
Basin Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SE/4, NE/4, Section 18, T28N, R11W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
30-045-24862  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5588' G. L.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 12-1/4" hole on 10-11-81 and drilled to 315'. Set 8-5/8" 24# surface casing at 315' on 10-11-81, and cemented with 315 sx of class "B" neat cement containing 2% CaCl<sub>2</sub>. Good cement was circulated to the surface. Drilled a 7-7/8" hole to a TD of 6270'. Set 4-1/2" 10.5# production casing at 6270', on 10-24-81, and cemented in two stages. 1) Used 410 sx of Class "B" neat cement containing 50:50 POZ, 6% gel, 2# medium tuf plug per sack, and .8% fluid loss additive. This was tailed in with 100 sx of class "B" neat cement. Good cement was circulated to the surface. 2) Used 810 sx of Class "B" neat cement containing 65:35 POZ, 6% gel, 2# medium tuf plug per sack, and .8% fluid loss additive. This was tailed in with 100 sx of class "B" neat cement. Good cement was circulated to the surface.

The DV tool was set at 4390'.

The rig was released on 10-24-81.

Subsurface Safety Valve: Manu. and Type 4/0 10 8/0 10 0 Set @ 1020 Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed By E. E. SYOBODA TITLE Dist. Admin. Supvr DATE 10/28/81

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD TITLE DATE  
CONDITIONS OF APPROVAL, IF ANY:

NOV 2 1981

\*See Instructions on Reverse Side

NMOCC

FARMINGTON DISTRICT

BY 545