

SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 965' FSL & 675' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

| TEST WATER SHUT-OFF | |
|----------------------|--|
| FRACTURE TREAT | |
| SHOOT OR ACIDIZE | |
| REPAIR WELL | |
| PULL OR ALTER CASING | |
| MULTIPLE COMPLETE | |
| CHANGE ZONES | |
| ABANDON* | |
| (other) | |

Well History

□ □ □ □ □ □ □

RECEIVED

DEC 17 1984

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT
WASHINGTON RESOURCE AREA

5. LEASE
SF-078904

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Gallegos Canyon Unit

8. FARM OR LEASE NAME

9. WELL NO.
337

10. FIELD OR WILDCAT NAME :
West Kutz Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA
Section 26 T28N-R12W

| | |
|----------------------------------|-------------------------|
| 12. COUNTY OR PARISH San Juan | 13. STATE New Mexico |
|----------------------------------|-------------------------|

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
G.L. Elev. 5907' - K.B. Elev. 5915'

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded @ 4:40 A.M., 12-6-84. Drilled 12 1/4 " hole to 155' and ran 3 jts 8 5/8", 20#, H-40. ST&C casing set at 145' K.B. Cemented w/100 sx Class "B" cement w/3% CaCl₂ + 1/4# Flocele/sx. Plug down 5:30 A.M. 12-7-84. Good cement returns.

Nippled up and pressure tested B.O.P.E. to 600 psi-held O.K. Drilled 6 1/4" hole to 1838' and ran logs. Ran 47 jts 4 1/2", 10.5#, K-55 ST&C casing set at 1826' K.B.

Cemented w/250 sx 50-50 Pozmix and cement w/2% gel, 1/2 of 1% CFR2, and 1/4# Flocele/sx. Plug down 11:40 A.M. 12-10-84. Good cement returns.
12-11-84 W.O.C. and W.O.C.T.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED N. D. Thomas TITLE Drilling Foreman DATE 12-11-84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

RECEIVED

DEC 31 1984

*See Instructions on Reverse Side

OIL CON. DIV. NMOC
DIST. 3

ACCEPTED FOR RECORD

DEC 28 1984

FARMINGTON RESOURCE AREA

RV