

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE  
(Other instructions on reverse side)

1. DATE OF REPORT  
2. NAME OF OPERATOR  
3. LEASE DESIGNATION AND SERIAL NO.

SF-078903

4. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use APPLICATION FOR PERMIT for such proposals.)

RECEIVED

JUN 03 1985

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

7. UNIT AGREEMENT NAME

Gallegos Canyon Unit

8. FARM OR LEASE NAME

9. WELL NO.

244 E

10. FIELD AND POOL, OR WILDCAT

Basin DK/Kutz GLP Ext

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SW/SW Sec 36, T28N, R12W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

6008' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

WELL OR S. TERMINATED

WATER SHUT-OFF

REPAIRING WELL

FRAC TURE TREAT

WELL DEEP COMPLETION

FRAC TURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANT

(Other) Spud and set casing

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud a 12-1/4" hole on 4-25-85. Drilled to 365'. Set 9-5/8", 36#, K55 casing at 359' and cemented with 295 Class B Portland. Circulated cement to surface. Pressure tested casing to 1000 psi for 30 minutes. Drilled an 8-3/4" hole to a TD of 6511' on 5-4-85. Set 7", 23#, K55 casing at 6511'. Stage 1: cemented with 424 cu. ft. Class B Portland and tailed in with 371 cu. ft. Class B portland. Stage 2: cemented with 863 cu. ft. Class B Portland. Circulated cement to surface after both stages.

The DV tool was set 3204' and the rig was released on 5-5-85.

18. I hereby certify that the foregoing is true and correct.

SIGNED

BDS Shaw

TITLE Adm. Supervisor

DATE 5-28-85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

NMOCC

JUN 03 1985